SCALETEC PLUS® Product Overview:

Scaletec Plus® Synertec™ formula utilizes advanced polymers, descalers and metal stain lifters for powerful cleanup action. Pool owners now have a more effective way to cleanup calcium scale and stains on pool surfaces, tile and equipment without acids and minimal scrubbing. Scaletec Plus enviro-safe, acid-free, low phosphorous formula is effective for both scale and stain removal. Most metal stains are quickly removed from surfaces within a few days or week depending on severity of metal stain.

Scale Removal - Quick Start Guide: Chlorine Pools:

- 1. Lower chlorine levels to within 1 to 3 ppm.
- 2. Add Scaletec Plus dosage (use chart) directly to pool water.
- 3. Operate pool recirculating pump as normal cycle.
- 4. Maintain chlorine levels at 1 to 3 ppm and pH at 7.2 to 7.8.

Scale Removal - Quick Start Guide: Salt Cell Pools:

- 1. Lower chlorine levels to within 1 to 3 ppm.
- 2. TURN OFF SALT CELL GENERATOR for 1 to 2 weeks.
- 3. Add Scaletec Plus dosage (use chart) directly to pool water.
- 3. Operate pool recirculating pump as normal cycle.
- 4. Maintain chlorine levels at 1 to 3 ppm and pH at 7.2 to 7.8.
- 5. Use liquid or chlorine tablets as alternate chlorine source.

DURING cleanup period (all pools):

- 1. Waterline calcium scales: raise and maintain water level above scale line. Scrubbing helps improve scale removal.
- 2. Do not shock pool with sanitizer during cleanup period.
- 3. For heavy or older scales, repeat dosages may be required.

AFTER cleanup period: use Beautec Scale and Stain Controller to continue cleaning surfaces and provide long lasting protection. Powerful Synertec® Concentrated Formulation





Removes Calcium / Waterline Scale / Metal Stains on Pool Surfaces, Tile and Equipment

Descales calcium scales and films without acid washing, draining or scrubbing

Removes metal stains and oil / scum buildup on surfaces

Restores the beauty and color brightness on pool finishes

64 FL. OZ. (1/2 U.S. Gallon / 1.89 litres) www.easycarewater.com

Made in U.S.A.

SCALETEC PLUS® TREATMENT CHART:

POOL SIZE (in U.S. gals. and litres)	CALCIUM / SCALE REMOVAL		STAIN REMOVAL
	FALL - SPRING	SUMMER	& WINTERIZING
10,000 (38,000 I)	32 oz. (1 litre)	64 oz. (2 litres)	32 oz. (1 litre)
15,000 (56,000 I)	48 oz. (1½ litres)	96 oz. (3 litres)	48 oz. (1½ litres)
20,000 (75,000 l)	64 oz. (2 litres)	128 oz. (4 litres)	64 oz. (2 litres)

DESCALING with **SCALETEC PLUS®** Easy steps to success!

- 1. Perform "spot check" to determine if deposit is primarily calcium based. Pour a capful of pool acid slowly over affected area. Active bubbling or foaming typifies newer calcium type scale and minimal reaction indicates harder. older scale. For these type of scales, additional product and time is usually required.
- 2. Add Scaletec Plus® according to chart. Use "summer dosage" for faster cleanup
- 3. Raise and maintain water level above scale line during entire cleanup period.
- 4. Operate pool pump daily 8 to 12 hours to improve cleanup activity.
- 5. DO NOT shock pool avoid high chlorine levels (above 3.0 ppm) during cleanup.
- 6. After cleanup (de-scaling) period, immediately lower water to normal level. Cleanup Tips:
- a) Salt chlorinators: lower chlorine level to 3 ppm or less and TURN OFF CHLORINATOR FOR 1 TO 2 WEEKS DURING INITIAL CLEANUP PERIOD.
- b) If de-scaling in summer, add additional dosage in 2 weeks.
- c) Older scale removal may require several treatments over 4 to 6 months.

IRON and METAL STAIN REMOVAL and PREVENTION:

To remove iron and other stains, add Scaletec Plus® directly to pool water. Operate pool pump's normal daily cycle. Minimize pool shocking. Brushing may aid in faster stain removal. Stain removal requires several days to one week or longer.

SCALE / SCUM PREVENTION and WINTER LAYUP:

For continuous cleaning and scale -stain prevention, add monthly maintenance dosage directly to pool water. Scaletec Plus® is compatible with all pool chemicals. June 2016 Add on separate days for best results. For winter scale-stain protection, add winter layup dosage at pool closing or at end of swim season for uncovered pools.

PRECAUTIONARY STATEMENTS:

CAUTION: May be harmful if swallowed as a concentrate. Avoid prolonged direct contact with skin, eyes and clothing.

FIRST AID: EYES: Immediately wash with cool water until thoroughly rinsed. SKIN: Rinse with water to remove all residue. Seek medical attention if necessary. IF SWALLOWED: Drink two glasses of water and contact a physician for guidance.

STORAGE & HANDLING: Keep container closed when not in use. Spills may be slippery. Mop up product with clean water. Do not blend directly with other pool chemicals.

DISPOSAL: Rinse container. Dispose in trash or recycle.

Visit our website at www.easycarewater.com or email us at mcgravel@mcgravel.com

Manufactured by: EasyCare® Products USA div. of McGrayel Co. Inc. 5361 S. Villa Avenue Fresno, CA 93725 U.S.A.



We are very proud of Scaletec Plus.™ If we can assist you. please call Customer Services Toll-Free, 24 hours 1-800-289-7660 (U.S.) or 1-559-299-7660.