

Product Overview:

Startup-tec's® New Pool Startup Treatment utilizes the "PK 3-Day" Startup Method. This new advanced startup sequestrant treatment significantly reduces calcium (dust) formation, staining, and tedious surface brushing on all types of plaster, cement and exposed aggregate finishes. Startup-tec® also helps reduce the amount of acid required to expose all types of aggregate finishes. Another exceptional feature of Startup-tec® is its ability to significantly reduce surface mottling and discoloration and provide for a more brilliant exposure.

Startup-tec's® strong multi-polymers create an easier, faster startup procedure for new or remodeled pools that produce a beautifully consistent surface finish. Startup-tec's advanced method creates superior results that allows the use of a new pool within just 3 days.

Startup-tec® initially provides powerful scale-stain protection for pool surfaces, tile and equipment. It is recommended to use Beautec Scale-Stain Controller after 30 days to continue this protection year-round.

STARTUP-TEC® is very effective on ...

Grey Finishes Quartz Aggregate
Color Pigment Exposed Aggregate
White Cement Pebble-Type Finishes

Startup-tec,® Beautec,® and EasyCare® are registered trademarks of McGrayel Company, Inc.

Powerful Synertec® Concentrated Formulation

STARTUP-TEC®



Proactive Startup Treatment for all Pools

Successfully tested at The National Pool Industry Research Center, California Polytechnic State University 2008-2009

- ★ Prevents and Removes Calcium / Plaster Dust Formation.
- ★ Powerful Sequestrants Reduce Brushing and Surface Mottling.
- ★ Brilliantly Exposes Colored and Aggregate Finishes with less Acids.
- ★ Protection Lasts Months to Prevent Scaling and Staining.

www.easycarewater.com

64 FL. OZ. (1/2 U.S. Gallon / 1.89 Litres)

Made in U.S.A.

STARTUP-TEC® TREATMENT CHART:

POOL SIZE (in U.S. gals. and liters)	STARTUP DOSAGES: (must add at initial filling)	
	WHITE, COLORED, EXPOSED QUARTZ, and PEBBLE TYPE FINISHES	WINTER STARTUP
10,000 (38,000 L)	32 to 64 oz. (1 to 2 liters)	64 to 128 oz. (2 to 4 L)
15,000 (56,000 L)	48 to 64 oz. (1 to 2 liters)	96 to 192 oz. (3 to 6 L)
20,000 (75,000 L)	64 to 128 oz. (2 to 4 liters)	128 to 256 oz. (4 to 8 L)

NOTE: Use of higher dosage is recommended for high hardness, well waters and colored pigmented finishes. Use higher winter dosage especially for color finishes.

DURING Pool Filling:

- For best results, check for low pH, alkalinity and/or hardness in fill water. Correct aggressive condition(s) within 48 hours of filled pool to prevent interior finish surface damage.
- At the 300 to 500 gallon level, add Startup-tec® "Startup Dosage" uniformly throughout basin as per pool size and type of finish.
- For all white and color marcite finishes, add Startup-tec® dosage at a minimum of 500 gallons or more..
- Add product using water can, PVC pipe or directly from bottle. uniformly into bowl area. Avoid splashing onto pool surfaces.
- Continue to fill pool without stopping the filling process.

AFTER Pool is Filled:

- Inspect pool surfaces. Lightly brush surfaces to remove any remaining calcium / plaster dust. Brush-vac to remove calcium in the pool basin area - do not use roller type vacuum.
- If necessary, perform a light-hot startup to obtain proper full exposure on exposed quartz or color pigmented finishes.
- For first few days, lightly brush all pool surface to remove any remaining calcium / plaster dust, dirt and loose debris.
- Balance pool water chemistries to obtain proper pH, alkalinity and hardness levels according to local needs.

IF FILLED POOL - WITHOUT STARTUP-TEC: Use the product Beautec® Scale-Stain Controller to remove calcium residual and prevent stains.

PRECAUTIONARY STATEMENTS:

CAUTION: May be harmful if swallowed as a concentrate. Avoid prolonged direct contact with skin, eyes and clothing.

FIRST AID: **EYES:** Immediately wash with cool water until thoroughly rinsed. **SKIN:** Rinse with water to remove all residue. Seek medical attention if necessary. **IF SWALLOWED:** Drink two glasses of water and contact a physician for guidance.

STORAGE & HANDLING: Keep container closed when not in use. Spills may be slippery. Mop up product with clean water.

DISPOSAL: Rinse container. Dispose in trash or recycle.

COMPOSITION: Multi-polymer formula technology

Visit our website at www.easycarewater.com
or email us at mcgrayel@mcgrayel.com

Manufactured by:

McGrayel Company, Inc.
EasyCare® Products Division
5361 S. Villa Avenue
Fresno, CA 93725 U.S.A.



We are very proud of Startup-tec.™ If we can assist you, please call Customer Services Toll-Free, 24 hours, 1-800-289-7660 (U.S.) or 1-559-299-7660.

Rev.
June 2016



48 oz / 1 litre

32 oz / litre

16 oz / 500 ml