



WHITE PVC TRUE UNION SPRING CHECK VALVE

RATED @200 PSI STATIC PRESSURE @ 72°F
MOLDED IN THE USA
MADE OF PVC TYPE I MATERIAL
EPDM WASHER & O-RING

IPS SLIP X IPS SLIP CONNECTION

IPS—IRON PIPE SIZE
(SAME AS SCH. 40 PIPE)



PART #	
OPEN PSI	FULL OPEN PSI

PART NUMBER		A (INCHES)	B (INCHES)	C (INCHES)	D (INCHES)	WEIGHT (LBS)	IPS CONNECTION
1/2# SPRING	2# SPRING						
1700-07	N/A	1.38	2.21	6.13	4.06	0.45	3/4" IPS
1.95 PSI							
1700-10	N/A	1.65	2.48	6.71	4.36	0.65	1" IPS
1.29 PSI 2.67 PSI							
1700-15	1702-15	2.25	3.34	8.22	5.12	1.20	1 1/4" IPS
0.79 PSI 2.17 PSI							
1700-20	1702-20	2.71	3.98	9.67	6.13	2.05	2" IPS
0.88 PSI 2.78 PSI							

NOTE: VALVE IS CONSIDERED OPEN WHEN SPRING IS COMPRESSED 1/8". FULL OPEN IS COMPLETE COMPRESSION OF SPRING.
FOR 1/2" AND 3/4" VALVES FULL OPEN IS APPROXIMATELY 1/8".
NOTE: LENGTH VARIES WITH TIGHTNESS OF END NUT
END NUT MAY BE WHITE OR GRAY

