



## LED 2030 (3.5 A / 20 AWG)

833.73.480	833.73.670
833.73.481	833.73.671
833.73.482	833.73.672
833.73.520	

12 V System	K	W	T <sub>A</sub>	mm	mm	
833.73.480	2700 K	4.8 W/m	-20 °C – +35 °C -4 °F – +95 °F	5000 x 8 x 2.3	≥ 18 x 12.3	= <div style="border: 1px solid black; padding: 2px; display: inline-block;">Loox 12 V</div>
833.73.670						
833.73.481	3000 K					
833.73.671						
833.73.482	4000 K					
833.73.672	5000 K					

732.28.390

**+**

833.73.775

**C**

833.73.730

**D**

833.73.736

x	
50	833.73.771
500	833.73.772
1000	833.73.773
2000	833.73.774

i

1

$X_1 + X_2 + \dots + X_n \leq X$

**i**

LED 2030	x <sub>n</sub> [m]	X [m]
12 V / 6 W	0.900	0.900
12 V / 15 W	2.400	2.400
12 V / 20 W	3.600	3.600
12 V / 27 W	4.300	4.300
12 V / 40 W	5.000	<b>7.200</b>
12 V / 60 W	5.000	<b>11.000</b>

HDE 11/2017

