

- In order to specify a Lid Stay, the Height and Weight of the door is needed
- The below chart should be used as a reference only as all weights are approximate
- Be sure to consider the weight of the handle to be used
- Manufacturer of the Door has to determine the correct weight for accuracy

3/4" (19mm) Particle Board - without handle

Width →	16"	20"	24"	28"	32"	36"	40"	44"	48"
Height ↓	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.
12"	3	4.2	4.8	5.7	7	7.3	8.1	9.0	9.7
14"	4	4.8	5.7	6.6	8	8.6	9.5	10.6	11.4
16"	4	5.5	6.6	7.7	9	9.7	10.8	11.9	13.0
18"	5	6.2	7.3	8.6	10	11.0	12.3	13.4	14.7
20"	6	6.8	8.1	9.5	11	12.3	13.6	15.0	16.3
22"	6	7.5	9.0	10.6	12	13.4	15.0	16.5	18.0
24"	7	8.1	9.7	11.4	13	14.7	16.3	18.0	19.6

Aluminum Framed Doors (example profile 1 3/4" x 7/8") with 4mm thick glass panel - without handle

Width →	16"	20"	24"	28"	32"	36"	40"	44"	48"
Height ↓	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.
12"	3.1	4.0	4.6	5.3	5.9	6.6	7.5	8.1	9
14"	3.7	4.4	5.3	6.2	6.8	7.7	8.6	9.2	10
16"	4.2	5.1	5.9	6.8	7.7	8.8	9.7	10.6	11
18"	4.6	5.5	6.6	7.7	8.8	9.7	10.8	11.9	13
20"	5.1	6.2	7.3	8.4	9.7	10.8	11.9	13.0	14
22"	5.5	6.8	7.9	9.2	10.6	11.7	13.0	14.3	16
24"	5.9	7.3	8.6	10.1	11.4	12.8	14.1	15.4	17