





## 14 oz. Solid Vinyl



General: solid fabric is a vinyl coated polyester Weight: 13 oz to 15 oz. per square yard (avg.) Resistance to Rot, Mildew & Fungus: Excellent Ultraviolet Resistance: Excellent Fire Retardant Ratings: NFPA 701, ASTM E84 Class A,

California State Fire Marshall (CSFM) Title 19



- 2" thick high impact foam with 7/16" Oriented Stand Board backing
- Fire-retardant vinyl in a variety of colors
- Pad assembly meets or exceeds ASTM F2440 for impact rated wall padding



- 2" thick high impact foam with 7/16" Oriented Stand Board backing
- Fire-retardant vinyl in a variety of colors
- Pad assembly meets or exceeds ASTM E-84 for Class A fire rated wall padding



- 2" thick fire-retardant and high impact foam with 7/16" Oriented Stand Board backing
- Fire-retardant vinyl in a variety of colors
- Pad assembly meets or exceeds ASTM E-84 for Class A fire rated wall padding
- · Pad assembly meets or exceeds ASTM F2440 for impact rated wall padding

## COLORCHART

Actual colors may vary slightly from samples



BI ACK BLACK 3C



**NAVY BLUE** PMS 533C



**ROYAL BLUE** 



LIGHT BLUE PMS 301U PMS 7459C



**PURPLE** PMS 669C



MAROON PMS 504C





ORANGE **PMS 200C** PMS 7417C



TAN PMS 4665C



YELLOW PMS 136C





FOREST GREEN KELLY GREEN PMS 3308U PMS 3298C



**GREY** PMS 424C

