



NOTE: FLOOR SLEEVES REQUIRED TO INSTALL SYSTEM. FLOOR SLEEVE COVER PLATES AVAILABLE IN BRASS AND CHROME FINISHES. FLOOR SLEEVES & COVER PLATES SOLD SEPARATELY.

PVB-1350 SYSTEM INCLUDES:

ITEM	QTY	DESCRIPTION	ID NUMBER
1	1	UPRIGHTS (PAIR) WITH WINCH	PVB-13U
2	1	NET (COLLEGIATE SIZE)	PVBN-3
3	1	SET ADJUSTABLE ANTENNAS (PAIR)	VBA-80
4	1	SET UPRIGHT PADDING (PAIR)	PVB-60P

UPRIGHT PADDING AVAILABLE IN THIRTEEN COLOR CHOICES
SPECIFY FROM SELECTION:

BLACK	FOREST GREEN	GRAY	KELLY GREEN	LIGHT BLUE	MAROON	NAVY BLUE	ORANGE	PURPLE	RED	ROYAL BLUE	TAN	YELLOW
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

PROJECT NAME _____

ARCHITECT _____

PROJECT NUMBER _____

CONTRACTOR _____



MULTI-PURPOSE INFINITELY ADJUSTABLE NET SYSTEM shall consist of two uprights with one winch, one competition net, and shall feature one set of antennas and one set of upright padding. System shall be supplied fully assembled.

ONE PIECE ALUMINUM UPRIGHTS (PVB-13U) shall provide infinitely adjustable net height settings by means of high quality sliding collars that accommodate required net heights for badminton, tennis, and volleyball. Uprights are designed to ensure a snug fit into 3.570" ID and 10" depth aluminum floor sleeves. Uprights shall be constructed of high tensile strength extruded aluminum tubing measuring 3.50" OD and 0.203" wall thickness, with a durable anodized finish. Winch and anchor straps shall be adjustable to accommodate varying sleeve installation widths. Upright base shall be constructed with a molded composite footing intended to protect finished flooring during transportation, storage, and installation of system. Individual upright weight shall not exceed 40 lbs.

NET TENSIONING WINCH (PVBWINCH) shall be constructed containing an internal worm gear featuring a high efficiency 10:1 turn ratio that shall eliminate snap back. The worm gear shall be completely enclosed within by means of a welded steel cover. Winch shall be furnished with a high quality folding handle. Winch shall be located on the lower section of the upright, exterior to the court for player safety.

COLLEGIATE NET (PVCN-3) shall be included with system. Net shall feature 4" polyester reinforced white vinyl head band. Net shall be fitted with a vinyl coated 0.125" VC 0.1875" top cable manufactured with a loop at either end and a 0.25" nylon bottom cable. Net shall be fitted with six net attachment straps with quick locking net strap buckles. Net shall utilize 4" #21 black nylon netting, UV stabilized & mildew resistant vinyl, and two net tension maintaining 0.375" OD steel end dowels that shall be enclosed within safety pockets.

ADJUSTABLE ANTENNAS (VBA-80) shall be included with this system.

UPRIGHT PADS (PVB-60P) shall be included with this system. Pads shall be constructed of 2" thickness polyurethane foam, covered with 14 oz vinyl coated nylon. Pad design shall allow for easy installation by means of a flexible hinge design and shall secure in place with hook and loop closure flaps. Pads are available in thirteen colors.