

Clydesdale Cut 18 Specifications and Warranties

$\overline{}$					
1-	Δ	n	Δ	ra	ı٠
u	┖-		┖.	ıa	Ι.

Description: Cut pile broadloom
Dye Method: Injection dyed
Dye Resolution: 256 dpi

Fiber: Premium Continuous Filament Nylon

Tufted Face Weight: 18 oz. / sq.yd.

Tuft Bind: Exceeds industry standards

Gauge: 1/10th
Pile Height: .186 in.

Primary Backing: Woven polypropylene

Secondary Backing: ActionBac

Secondary Backing (optional): KangaTRAC polyurethane cushion Delamination: Exceeds industry standards

Anti-Soil and Stain Protection: Impervion® soil and stain treatment

Antimicrobial Protection: Impervion® mold, mildew, and odor treatment

Broadloom Width: 12'
Origin: U.S.A.

Performance:

Static Electricity: less than 3.5kv (permanent anti-static fiber)

Traffic: Commercial

Indoor Air Quality: Green Label Plus Certified

Flammability:

Radiant Panel: Class I

NBS Smoke Chamber: less than 450

Maintenance:

Spot Cleaning: Spot clean with approved carpet cleaner. Follow

manufacturer recommendations. Vacuum regularly.

Professional Cleaning: Hot water extraction.

Warranties:

Limited Lifetime Commercial Wear Warranty Limited Manufacturer Defects Warranty Lifetime Antistatic Control Fade Resistance (for indoor use only) 100% Recyclable