

# 15 Gallon, Portable Self-Contained Hughes Eyewash Station, Pressurized - 15GEW

#### **Product Images**







#### **Short Description**



Justrite Safety Group

- 15 US gallon (56.8 liter) stainless steel pressure vessel with built in carrying handles, provides emergency eye washing for up to 15 minutes
- Pop-off dust covers and push lever operation for ease of use
- Pressure gauge and dual action safety valve prevent over pressurization and allow the user to vent the cylinder for cleaning and maintenance
- Includes ANSI-compliant identification sign on activation lever and inspection tag for recording test and service history
- Use integral 1/2-in (F) NPT connection to attach optional drench hose OPT50 for decontamination of body parts subjected to minor exposure

## **Description**

Cost-effective, ANSI-compliant solution for locations that are unsuitable for fixed installations or those without access to a plumbed-in water supply.

# **Specifications**

| Model No                        | 15GEW  |
|---------------------------------|--|
| Color                           | Green  |
| UPC                             | 697841269941   |
| Capacity                        | 15 gallon  |
| Liter Capacity                  | 56.8   |
| Net Weight, lbs                 | 44   |
| Net Weight, kg                  | 20   |
| Filled Weight, lbs              | 127  |
| Filled Weight, kg               | 57.8   |
| Dimensions, Exterior            | 41.2" H x 15.9" W x 15.9" D  |
|                                 | 1047mm H x 404mm W x 404mm D   |
| Water Inlet Size NPT            | 1/2 in (F)   |
| Minimum Operating Pressure      | 2.1 bar g, 30 PSI  |
| Maximum Operating Pressure      | 5.5 bar g, 80 PSI  |
| Water Flow Eye/Face Liters/min  | 1.5  |
| Water Flow Eye/Face US Gal/min  | 0.4  |
| Material Specifications         | Body: Stainless Steel, Eye/facewash diffusers: Chrome plated brass with stainless steel mesh |
| Operating Valve Material        | 316L Stainless   |
| Pipework Material               | Stainless Steel  |
| Activation Method               | Push Plate   |
| Minimum Ambient Temperature, °F | 41   |
| Minimum Ambient Temperature, °C | 5  |
| Maximum Ambient Temperature, °F | 95   |
| Maximum Ambient Temperature, °C | 35   |
| Operation Duration, min         | 15   |
|                                 |  |

7/10/24

## Prop 65

▲WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.