

Floor Mount, Open ABS Bowl, Laboratory Hughes Combination Shower, Stainless Steel Pipe - L18GS34G

Product Images



Short Description

HUGHES



Justrite Safety Group

- Powder coated stainless steel pipework, bowl, and rose ensures resistance to corrosive and flammable materials
- Easy to clean
- High-performance quarter-turn ball valves made of 316L stainless steel endure the harshest environments and site conditions
- Includes a universal eye wash and safety shower sign for enhanced visibility
- Meets ANSI Z358.1 2014 and EN 15154 standards, supports OSHA requirements

Description

Ideal for laboratories, schools and general light duty indoor use, this floor mounted emergency combination shower is suitable for use in applications that are not subject to the possibility of freezing or overheating.

The system features specially designed valves with low operating torque offering reliable, easy on/off operation when emergencies occur. Valve includes an integral, heavy-duty stainless steel stop-plate to handle rough operation without failure. Low operating torque offers reliable, easy on/off operation. Durable, coated stainless steel shower pull handle with nylon valve connection is easy to grip and activate for immediate water drenching from the shower rose that is designed for high flow rates.

Open bowl eye/face wash with high, ANSI-compliant flow rate includes aerated diffusers with fine mesh strainers and an individual flow controller which provide a soft, scrubbing action to the eyes and face. Features twin spray nozzles with dust covers that pop-off when eye wash is activated via the push plate. Easy-to-reach flow regulator valve adjusts to suit the severity of the accident. Highly visible red push plate with universal hand and eye wash sign for simple activation. Includes an inspection record tag for recording test and service history. Add optional foot treadle for a secondary means of eyewash activation. Some assembly may be required.

Specifications

Model No	L18GS34G
Color	Green
UPC	805042000373
Net Weight, lbs	33.1
Net Weight, kg	15
Dimensions, Exterior	101" H x 12.6" W x 32.7" D 2566mm H x 319mm W x 319mm D
Height Without Sign, inches	91.5
Height Without Sign, mm	2324
UL Classified to ANSI Z358.1-2014	Yes
Water Inlet Size NPT	1 in (M)
Minimum Operating Pressure	2 bar g, 29 PSI
Maximum Operating Pressure	6 bar g, 87 PSI
Water Flow Shower/Body Liters/min	76
Water Flow Shower/Body US Gal/min	20
Water Flow Eye/Face Liters/min	11.4
Water Flow Eye/Face US Gal/min	3
Material Specifications	Rose: Powder coated stainless steel, Eye/facewash diffusers: Chrome plated brass with stainless steel mesh.
Operating Valve Material	316L Stainless
Eye/Face Wash Bowl Material	Powder-Coated Stainless Steel
Mounting Type	Floor
Pipework Material	Stainless Steel
Activation Method	Shower: Pull Handle, Eye/Face wash: Push Plate
Eye/Face Wash Bowl Interior Dimensions	10.25" W x 10.25" D 260mm W x 260mm D

Rose Diameter, inches	10
Rose Diameter, mm	254
Minimum Ambient Temperature, °F	41
Minimum Ambient Temperature, °C	5
Maximum Ambient Temperature, °F	95
Maximum Ambient Temperature, °C	35

Prop 65

⚠️WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.