

# Product information

## Truck Series DPF Protector

PI 6/14/09/2020



### Description

An effective mixture of additives that reduce soot formation during combustion while improving engine performance and reducing emissions. Reduces premature clogging of the DPF by soot and extends the DPF regeneration intervals.

### Properties

- reduces soot emissions
- regeneration aid for diesel particulate filters
- especially suitable for short trips and city vehicles

### Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellbraun, klar / light brown, clear
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	145 °F
Pour point	- 97 °F
Form	flüssig / liquid
Odor	charakteristisch / characteristic

### Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF).

### Application

Contents (500 mL) is sufficient for 50-115 Liters (14 gal. to 30 gal.) diesel. For best results and long-term effect add DPF protector every 2.000 km (1.200 miles).

### Comment

 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### Available pack sizes

500 ml Can sheet metal 20258  
USA (-EN-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**