

Product information

Marine Super Diesel Additive

PI 23/14/09/2020



Description

A combination of additives that clean and maintain diesel fuel systems. Prevents corrosion and increases lubrication thus reducing fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order.



Properties

- boosts the cetane number
- keeps the fuel system clean
- optimizes engine performance
- keeps injector nozzles clean
- guarantees low fuel consumption
- very wear resistant
- prevents the build-up of deposits
- increases the lubricating effect
- prevents seizing and the injector needles from gumming up

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in carrier fluid
Color / appearance	gelb-braun / yellowish brown
Density at 59 °F	0,87 g/cm ³
Hazard class as per German VbF	A III
Flash point	145 °F
Pour point	-33 °F

Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF).

Application

Contents (500 mL) is sufficient for 250 Liters (66 gal.) diesel fuel (mixing ratio 1: 500). Fluid is self mixing.

Comment

 **WARNING:** Cancer - www.P65Warnings.ca.gov.

Available pack sizes

500 ml Can sheet metal	20550
	USA (-EN-)
500 ml Can sheet metal	20526
	CANADA (-EN-F-)
1 l Can sheet metal	20552
	USA (-EN-)

Our information is based on thorough research and may be considered reliable, although not legally binding.