# **SAFETY DATA SHEET**

KDQ5616

## Section 1. Identification

Product name	: KRYLON® CoverMaxx™ Gloss Banner Red	
Product code	: KDQ5616	
Other means of identification	Not available.	
Product type	: Liquid.	
Relevant identified uses of t	he substance or mixture and uses advised against	
Paint or paint related material.		
Manufacturer	: Krylon Products Group 101 W. Prospect Avenue Cleveland, OH 44115	
Emergency telephone number of the company	: US / Canada: (216) 566-2917 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year	
Product Information Telephone Number	: US / Canada: (800) 457-9566 Mexico: Not Available	
Regulatory Information Telephone Number	: US / Canada: (216) 566-2902 Mexico: Not Available	
Transportation Emergency Telephone Number	: US / Canada: (216) 566-2917 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year	

## Section 2. Hazards identification

KDQ5616 KRYLON® Cov Banner Red		SHW-85-NA-GHS-U	
Storage Date of issue/Date of revision	: Store locked up. : 3/10/2021 Date of previous issue : 2/2/2021	Version : 5	1/12
Response	: IF exposed or concerned: Get medical advice or attention.		
Prevention	: Obtain special instructions before use. Do not handle until a been read and understood. Wear protective gloves, protect protection.	5.	
General	: Read label before use. Keep out of reach of children. If me have product container or label at hand.		
Precautionary statements			
Hazard statements	: May cause genetic defects. May damage fertility or the unborn child.		
Signal word	: Danger		
<u>GHS label elements</u> Hazard pictograms	:		
Classification of the substance or mixture	: GERM CELL MUTAGENICITY - Category 1 TOXIC TO REPRODUCTION - Category 1B		
OSHA/HCS status	<ul> <li>This material is considered hazardous by the OSHA Hazard (29 CFR 1910.1200).</li> </ul>	Communication Star	

## Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

### Substance/mixture

**CAS number/other identifiers** 

: Mixture : Not available.

## Other means of identification

Ingredient name	% by weight	CAS number
Heavy Paraffinic Oil	≤0.3	64742-65-0
Carbendazim	≤0.3	10605-21-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of neces	sary first aid measures
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Date of issue/Date	of revision	: 3/10/2021	Date of previous issue	: 2/2/2021	Version : 5	2/12
KDQ5616	KRYLON® CoverMaxx Banner Red	t™ Gloss			SHW-85-NA-GHS-US	

## Section 4. First aid measures

ts		
: No known significant effects or critical hazards.		
: No known significant effects or critical hazards.		
: No known significant effects or critical hazards.		
: No known significant effects or critical hazards.		
<u>toms</u>		
: No specific data.		
: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations		
: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations		
: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations		
lical attention and special treatment needed, if necessary		
: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.		
: No specific treatment.		
: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		

#### See toxicological information (Section 11)

Banner Red

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Date of issue/Date of revision	: 3/10/2021 Date of previous issue : 2/2/2021 Version : 5 3.
KDQ5616 KRYLON® Cove	Maxx™ Gloss SHW-85-NA-GHS-US

### Section 5. Fire-fighting measures

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste

disposal contractor.
 Large spill
 Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

Precautions for safe handli	ng
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

: 2/2/2021

## Section 7. Handling and storage

Conditions for safe storage,	1	Store in accordance with local regulations. Store in original container protected from
including any		direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials
incompatibilities		(see Section 10) and food and drink. Store locked up. Keep container tightly closed
-		and sealed until ready for use. Containers that have been opened must be carefully
		resealed and kept upright to prevent leakage. Do not store in unlabeled containers.
		Use appropriate containment to avoid environmental contamination. See Section 10 for
		incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Heavy Paraffinic Oil	64742-65-0	OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours. ACGIH TLV (United States, 3/2020). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist
Carbendazim	10605-21-7	None.

#### **Occupational exposure limits (Canada)**

Ingredient name	CAS #	Exposure limits
Kaolin	1332-58-7	<ul> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> <li>CA British Columbia Provincial (Canada, 1/2020). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> <li>CA Quebec Provincial (Canada, 7/2019). TWAEV: 5 mg/m<sup>3</sup> 8 hours. Form: Respirable dust.</li> <li>CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 4 mg/m<sup>3</sup> 15 minutes. Form: respirable fraction TWA: 2 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</li> </ul>

#### **Occupational exposure limits (Mexico)**

2

	CAS #	Exposure limits
None.		

## Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

 $\overline{\phantom{a}}$ 

## Environmental exposure controls

Date of issue/Date	e of revision	: 3/10/2021	Date of previous issue	: 2/2/2021	Version : 5	5/12
KDQ5616 KRYLON® CoverMaxx <sup>™</sup> Gloss			SHW-85-NA-GHS-US			
	Banner Red					

## Section 8. Exposure controls/personal protection

	• •
	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection :	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection :	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection :	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection :	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9
Melting point/freezing point	: Not available.
Boiling point/boiling range	: 100°C (212°F)
Flash point	: Closed cup: 96°C (204.8°F) [Pensky-Martens Closed Cup]
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: 2.3 kPa (17.5 mm Hg) [at 20°C]
Vapor density	: 1 [Air = 1]
Relative density	: 1.04

Date of issue/Date	of revision	: 3/10/2021	Date of previous issue	: 2/2/2021	Version : 5	6/12
KDQ5616	KRYLON® CoverM Banner Red	axx™ Gloss			SHW-85-NA-GHS-US	

## Section 9. Physical and chemical properties

Solubility	: Not available.	
Partition coefficient: n- octanol/water	: Not available.	
Auto-ignition temperature	: Not available.	
Decomposition temperature	: Not available.	
Viscosity	: Kinematic (40°C (104°F)): >0.205 cm²/s (>20.5 cSt)	
Molecular weight	: Not applicable.	
Aerosol product		
Heat of combustion	: 1.07 kJ/g	

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Heavy Paraffinic Oil	LD50 Dermal	Rabbit	>5000 mg/kg	-
-	LD50 Oral	Rat	>5000 mg/kg	-
Carbendazim	LD50 Dermal	Rabbit	8500 mg/kg	-
	LD50 Dermal	Rat	2 g/kg	-
	LD50 Oral	Rat	>5050 mg/kg	-

#### Irritation/Corrosion

Not available.

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Date of issue/Date of revision KDQ5616 KRYLON® CoverMa

## Section 11. Toxicological information

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Banner Red

Not available.

#### Aspiration hazard

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	:	Not available.	
Potential acute health effe	cts		
Eye contact		No known significant effects or critical hazards.	
Inhalation	:	No known significant effects or critical hazards.	
Skin contact	:	No known significant effects or critical hazards.	
Ingestion	:	No known significant effects or critical hazards.	
Symptoms related to the p	ohy	sical, chemical and toxicological characteristics	
Eye contact	1	No specific data.	
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Delayed and immediate eff	fec	ts and also chronic effects from short and long term exposure	

: 3/10/2021 Date of previous issue : 2/2/2021 Version : 5	8/12
: May damage the unborn child.	
: May cause genetic defects.	
: No known significant effects or critical hazards.	
: No known significant effects or critical hazards.	
ects	
: Not available.	
: Not available.	
: Not available.	
: Not available.	
	<ul> <li>Not available.</li> <li>Not available.</li> <li>Not available.</li> <li>ects</li> <li>No known significant effects or critical hazards.</li> <li>No known significant effects or critical hazards.</li> <li>May cause genetic defects.</li> <li>May damage the unborn child.</li> </ul>

### Section 11. Toxicological information

Developmental effects Fertility effects No known significant effects or critical hazards.May damage fertility.

Numerical measures of toxicity Acute toxicity estimates

Not available.

## Section 12. Ecological information

-			A	
	ΟΧΙ	С	τν	
			_	

Product/ingredient name	Result	Species	Exposure
Carbendazim	Acute EC50 19.0562 mg/l Fresh water	Algae - Scenedesmus acutus var. acutus	96 hours 🥄
	Acute EC50 20 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 77 µg/l Fresh water	Crustaceans - Gammarus pulex - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 7 µg/l Fresh water	Fish - Ictalurus punctatus - Yolk- sac fry	96 hours
	Chronic EC10 10 µg/l Fresh water	Crustaceans - Gammarus pulex - Adult	21 days
	Chronic NOEC 3.1 ppb Fresh water	Daphnia - Daphnia magna	21 days

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Carbendazim	-	2.51	low 🥄

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date	of revision	: 3/10/2021	Date of previous issue	: 2/2/2021	Version : 5	9/12
KDQ5616	KRYLON® CoverMaxx Banner Red	™ Gloss			SHW-85-NA-GHS-US	

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No. 🥄	No.
Additional information	-	-	-	-	-
Special precautions ransport in bulk ac	conside mode o suitably prior to respons unloadin substan	er container sizes. The f transport (sea, air, for that mode of transhipment, and composibility of the person and dangerous goods inces and on all action	e presence of a shi etc.), does not indic nsport. All packaging liance with the appli offering the product must be trained on	for informational purp pping description for ate that the product is g must be reviewed f icable regulations is for transport. People all of the risks derivi ency situations.	a particular is packaged for suitability the sole loading and

Proper shipping name : Not available.

## Section 15. Regulatory information

#### SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations	
International lists	: Australia inventory (AICS): Not determined. China inventory (IECSC): Not determined.
	Japan inventory (ENCS): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.


Date of issue/Date	of revision	: 3/10/2021	Date of previous issue	: 2/2/2021	Version	:5	10/12
KDQ5616	KRYLON® CoverMaxx <sup>†</sup> Banner Red	™ Gloss			SHW-85-	NA-GHS-US	

### Section 15. Regulatory information

Vietnam inventory: Not determined.

## Section 16. Other information





The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

#### Procedure used to derive the classification

	Classification	Justification
GERM CELL MUTAGENIC TOXIC TO REPRODUCTI	Calculation method Calculation method	
History		
Date of printing	: 3/10/2021	
Date of issue/Date of revision	: 3/10/2021	
Date of previous issue	: 2/2/2021	
Version	: 5	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification a IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeff MARPOL = International Convention for the Prevention as modified by the Protocol of 1978. ("Marpol" = marine N/A = Not available SGG = Segregation Group UN = United Nations	icient of Pollution From Ships, 1973

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user

Date of issue/Date	of revision	: 3/10/2021	Date of previous issue	: 2/2/2021	Version : 5	11/12
	KRYLON® CoverMaxx Banner Red	™ Gloss			SHW-85-NA-GHS-US	

## Section 16. Other information

should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.