



## Scotch-Brite™ Durable Flex Belt

Aggressive and long-lasting non-woven belt is reinforced with low stretch backing for durability. Produces a fine and consistent finish. Great for general surface prep for welding and adhesive bonding. Cleans welds and hot spots. Feathers edges for plastic repair.

Part No.	Grade	W x L	Belts per Case
<b>77257</b>	A CRS		
<b>77256</b>	A MED	3/8" x 13"	40
<b>77255</b>	A FIN		
<b>64475</b>	A CRS		
<b>66458</b>	A MED	1/2" x 18"	20
<b>64467</b>	A FIN		

For tools, see page 10.



3M™ Mini File Belt Sander 33573



3M™ File Belt Sander 33575



3M™ Heavy-Bodied Seam Sealer 08308



3M™ Panel Bonding Adhesive 08115

**Related Products**  
Learn more at [3MCollision.com](http://3MCollision.com)

# 3M™ Body Repair Tools

## 3M™ Mini File Belt Sander and File Belt Sander

3M™ File Belt Sanders allow technicians to access hard-to-reach areas and are great for spot weld removal, deburring, cleaning, and finishing. Remove spot welds cleanly and quickly with 3M™ Cubitron™ II File Belts — replacing the need for expensive drills and bits. Adjustable arm for user comfort and multiple applications. Available in 13" and 18" sizes.



Part No.	Belt Size in (mm)	Max RPM	Weight lb (kg)	Height in (mm)	Length in (mm)	Motor hp (W)
Belt Speed: 4100 SFPM (1250 SMPM)						
<b>33573</b>	3/8 × 13 (10 × 330)	17,000	2.07 (0.94)	2.87 (73)	12.50 (320)	0.65 (485)
<b>33575</b>	1/2 × 18 (13 × 457)		2.16 (0.98)		15.15 (385)	

For belts, see pages 4–5.

## 3M™ Cut-Off Wheel Tools

3M™ Cut-Off Wheel Tools deliver the performance you need when working with tough automotive substrates. When paired with 3M™ Cubitron™ II Cut-Off Wheels, technicians can even slice through high-strength steel and aluminum with clean, straight lines and minimal effort. Power with a Cubitron II cut-off wheel for a cleaner cut that runs cooler. Compact design with built-in safety features for easy handling. Featuring a light-weight composite body for greater user comfort. Available in 3" and 4" sizes.



Part No.	Wheel Size in (mm)	Max RPM	Thread Size	Weight lb (kg)	Height in (mm)	Length in (mm)	Motor hp (W)
ALWAYS USE WITH GUARD							
<b>33579</b>	3 (75)	20,000	1/4" – 28	1.91 (0.87)	3.14 (79.6)	7.73 (196)	0.70 (522)
<b>33581</b>	4 (100)			2.00 (0.91)	3.42 (86.9)		

For wheels, see page 8.

## Related Products

Learn more at [3MCollision.com](http://3MCollision.com)



3M™ Cubitron™ II File Belt 33437



3M™ Cubitron™ II Cut-Off Wheel 33456



3M™ Cubitron™ II Fibre Roloc™ Disc 33389



3M™ Panel Bonding Adhesive 08115