Ontinental

3/8" ID Yellow Rubber Air Hose

Tough double-braid wall construction, BPT rated at 1000 burst. 1/4" NPT connections. Genuine rubber with patented reinforced weave of nylon cord. Now Continental, formerly Goodyear, same great quality and guarantee.

- Tough double-braid wall construction
- Fully reinforced nylon cord weave
- Genuine rubber construction

Specifications
Connection: 1/4" NPT (M)
Hose ID: 3/8"





AES-7367

INDIVIDUALLY BUNDLED





3/8" ID Hybrid Air Hose

This lightweight UV and Ozone resistant hose looks and feels like rubber but has the chemical resistance of PVC RMA Class (A) and (B) oil resistance. It has a non-marring, silicone-free tube and cover. 1/4" NPT threaded brass ends. It has great cold weather flexibility down to -15° F and will operate continuously up to +150° F.

INDIVIDUALLY BUNDLED

SKU	Length
AES-8263	25'
AES-8265	50'
AES-8269	100'



Specifications	
Thread Size:	1/4" NPT (M)
Hose ID:	1/4"
Max. Working Pressure:	120 PSI



1/4" ID Nylon Self-Recoil Air Hose

Super lightweight nylon air hose includes 360° swivel male fittings at both ends. 1/4" NPT male swivel fittings. Abrasive resistant.

SKU	Length
AES-1425	25'
AES-1450	50'

INDIVIDUALLY BAGGED Specifications	
Hose ID:	1/4"
Max. Working Pressure:	120 PSI



1/4" ID Polyurethane Recoil Air Hose

These polyurethane air hoses are designed and built for professional applications requiring easy-access air supply and automatic recoil under frequent use.

SKU	Length
AES-51425	25'
AES-51450	50'

Specifications	
Thread Size:	1/4" NPT (M)
Hose ID:	1/4"
Max. Working Pressure:	120 PSI



3/8" ID Polyurethane Recoil Air Hose

Heavy-duty, recoil air hose is lighter than rubber hose. Extremely flexible and kink resistant. Reusable brass male swivel fittings on each end.

SKU	Length
AES-53825	25'
AES-53850	50'

INDIVIDUALLY BAGGED	
Specifications	
Thread Size:	1/4" NPT (M)
Hose ID:	3/8"
Max. Working Pressure:	120 PSI

Replacement Tank Drain Valve AES-1853

OEM compressor tank drain valve replacement. Pre-applied thread sealant for air tight connections. Replaces old leaky or stripped tank drain valves.



