GU GEARWRENCH

10 Pc. 1/4 and 3/8" Drive Torx[®] Stubby Bit Driver Set

- Short overall length provides better access in tight spaces
- S2 steel for strength and durability
- Hard stamped size markings
- Satin finish for corrosion protection and simple cleaning
- Compact design provides additional access compared to standard
- bit sockets Includes socket rail for storage and organization



Cat. No.	Included Storage	Product Weight			~
81196	Socket Rail	0.46 lb			C
Cat. No.	Description		Cat. No.	Description	
81184	1/4" Drive Stubby Torx®	Bit Driver Socket T10	81189	1/4" Drive Stubby Torx® Bit Driver Socket T30	
81185	1/4" Drive Stubby Torx®	Bit Driver Socket T15	81190	1/4" Drive Stubby Torx® Bit Driver Socket T40	
81186	1/4" Drive Stubby Torx®	Bit Driver Socket T20	81191	3/8" Drive Stubby Torx® Bit Driver Socket T45	
81187	1/4" Drive Stubby Torx®	Bit Driver Socket T25	81192	3/8" Drive Stubby Torx® Bit Driver Socket T47	
81188	1/4" Drive Stubby Torx®	Bit Driver Socket T27	81193	3/8" Drive Stubby Torx® Bit Driver Socket T50	

13 Pc. 1/4", 3/8", and 1/2" Drive Torx[®] Tamper Proof Bit Socket Set

Product Weight

- Heat treated for maximum durability
- Bits made of S2 steel for strength and durability
- Bright, full polish chrome finish easily wipes clean and resists corrosion
- Hard stamped size markings

Cat. No.

Includes socket rail for storage and organization

Included Storage

Meets or exceeds ASME specifications



80725	Socket Rail	1.38 lb			C
Cat. No.	Description		Cat. No.	Description	
80178	1/4" Drive Tamper-Proof Torx®	Bit Socket T7	80185	1/4" Drive Tamper-Proof Torx® Bit Socket T30	
80179	1/4" Drive Tamper-Proof Torx®	Bit Socket T8	80456D	3/8" Drive Tamper-Proof Torx® Bit Socket T40	
80180	1/4" Drive Tamper-Proof Torx®	Bit Socket T10	80457	3/8" Drive Tamper-Proof Torx® Bit Socket T45	
80181	1/4" Drive Tamper-Proof Torx®	Bit Socket T15	80458	3/8" Drive Tamper-Proof Torx® Bit Socket T50	
80182	1/4" Drive Tamper-Proof Torx®	Bit Socket T20	80459	3/8" Drive Tamper-Proof Torx® Bit Socket T55	
80183	1/4" Drive Tamper-Proof Torx®	Bit Socket T25	80668	1/2" Drive Tamper-Proof Torx $^{\ensuremath{\circledast}}$ Bit Sockets T60	
80184	1/4" Drive Tamper-Proof Torx®	Bit Socket T27			

11 Pc. 1/4" and 3/8" Drive Universal Stubby Tamper Proof Torx[®] Bit Socket Set

- For use with tamper proof security fasteners
- Universal joint allows for greater access
- Bits made of S2 steel for strength and durability
- Hard stamped size markings
- Bright, full polish chrome finish easily wipes clean and resists corrosion Includes socket rail for storage and organization

Cat. No.	Included Storage	Product Weight
81052	Socket Rail	1.30 lb
Cat. No.	Description	
81040	1/4" Drive Universal Stub	by Tamper Proof Torx® Bit Socket T8
81041	1/4" Drive Universal Stub	by Tamper Proof Torx® Bit Socket T10
81042	1/4" Drive Universal Stub	by Tamper Proof Torx® Bit Socket T15
81043	1/4" Drive Universal Stub	by Tamper Proof Torx® Bit Socket T20
81044	1/4" Drive Universal Stub	by Tamper Proof Torx® Bit Socket T25
81045	1/4" Drive Universal Stub	by Tamper Proof Torx® Bit Socket T27

13 Pc. 1/4", 3/8", and 1/2" Drive External Torx[®] Socket Set

- For use with external Torx[®] fasteners
- Black oxide finish is corrosion resistant
- Heat treated socket for durability
- Hard stamped size markings
- For use with manual drive tools only
- Includes socket rail for storage and organization

Cat. No.	Included Storage	Product Weight
80583	Socket Rail	2.08 lb
Cat. No.	Description	
80186	1/4" Drive External Torx® Socket	E4
80187	1/4" Drive External Torx® Socket	E5
80188D	1/4" Drive External Torx® Socket	E6
80189	1/4" Drive External Torx® Socket	E7
80190	1/4" Drive External Torx® Socket	E8
80460	3/8" Drive External Torx® Socket	E10
80461	3/8" Drive External Torx® Socket	E12

MULTI-DRIVE



 \odot

RATCHETS

SOCKETS

Cat. No.	Description
81046	1/4" Drive Universal Stubby Tamper Proof Torx® Bit Socket T30
81047	3/8" Drive Universal Stubby Tamper Proof $\ensuremath{Torx}^{\circledast}\ensuremath{Bit}$ Socket T40
81048	3/8" Drive Universal Stubby Tamper Proof $\ensuremath{Torx}^{\circledast}\ensuremath{Bit}$ Socket T45
81049	3/8" Drive Universal Stubby Tamper Proof $\ensuremath{Torx}^{\circledast}\ensuremath{Bit}$ Socket T50
81050	3/8" Drive Universal Stubby Tamper Proof $\ensuremath{Torx}^{\circledast}$ Bit Socket T55




Cat. No.	Description
80462	3/8" Drive External Torx [®] Socket E14
80463	3/8" Drive External Torx® Socket E16
80669D	1/2" Drive External Torx [®] Socket E18
80670	1/2" Drive External Torx [®] Socket E20
80672	1/2" Drive External Torx [®] Socket E22
80673	1/2" Drive External Torx [®] Socket E24

FORGE AHEAD

GEARWRENCH

3/8" Drive Torx[®] Bit Sockets

- Heat-treated socket base for durability
- S2 steel insert bits offer maximum strength
- Double line (SAE) and knurled (metric) ring help easily identify standard and metric sockets
- Hard stamped size markings
- Bright, full polish chrome finish easily wipes clean and resists corrosion
- Meets or exceeds ASME specifications



Cat. No.	Fastener Size	Dim. A: Drive End	Dim. B: Nose Diameter	Dim. C: Overall Length	Dim. D: Bit Length	Product Weight
80534	T15	0.688 in	0.590 in	1.85 in	0.984 in	0.12 lb
80535	T20	0.688 in	0.590 in	1.85 in	0.984 in	0.12 lb
80536	T25	0.688 in	0.590 in	1.85 in	0.984 in	0.14 lb
80537	T27	0.688 in	0.590 in	1.85 in	0.984 in	0.15 lb
80538	T30	0.688 in	0.590 in	1.85 in	0.984 in	0.15 lb
80451	T40	0.688 in	0.590 in	1.85 in	1.181 in	0.18 lb
80452	T45	0.688 in	0.590 in	1.85 in	1.181 in	0.18 lb
80453	T47	0.688 in	0.590 in	1.85 in	1.181 in	0.18 lb
80454	T50	0.688 in	0.590 in	1.85 in	1.181 in	0.20 lb
80455	T55	0.688 in	0.590 in	1.85 in	1.181 in	0.20 lb



- Heat-treated socket base for durability
- S2 steel insert bits offer maximum strength
- Double line (SAE) and knurled (metric) ring help easily identify standard and metric sockets
- Hard stamped size markings
- Bright, full polish chrome finish easily wipes clean and resists corrosion
- Meets or exceeds ASME specifications

				0
n.	D: Bolt Clearance	Pr	roduct Weig	ht

Cat. No.	Fastener Size	Dim. A: Drive End	Dim. B: Nose Diameter	Dim. C: Overall Length	Dim. D: Bolt Clearance	Product Weight
82517	T40	0.688 in	0.590 in	5.984 in	5.196 in	0.45 lb
82518	T45	0.688 in	0.590 in	5.984 in	5.196 in	0.48 lb
82519	T50	0.688 in	0.590 in	5.984 in	5.196 in	0.52 lb

3/8" Drive Stubby Torx[®] Bit Drivers

- Short overall length provides better access in tight spaces
- S2 steel for strength and durability
- Hard stamped size markings
- Satin finish for corrosion protection and simple cleaning
- Compact design provides additional access compared to standard bit sockets
- Includes socket rail for storage and organization

Cat. No.	Fastener Size	Dim. A: Drive End	Dim. C: Overall Length	Dim. D: Bit Length	Product Weight
81191	T45	0.701 in	1.44 in	-	0.07 lb
81192	T47	0.701 in	1.44 in	-	0.07 lb
81193	T50	0.701 in	1.44 in	.312 in	0.07 lb

3/8" Drive Tamper Proof Torx[®] Bit Sockets


- Heat-treated socket base for durability
- S2 steel insert bits offer maximum strength
- Double line (SAE) and knurled (metric) ring help easily identify standard and metric sockets
- Hard stamped size markings
- Bright, full polish chrome finish easily wipes clean and resists corrosion Meets or exceeds ASME specifications

Cat. No.	Fastener Size	Dim. A: Drive End	Dim. B: Nose Diameter	Dim. C: Overall Length	Dim. D: Bit Length	Product Weight
80456D	T40	0.688 in	0.590 in	1.85 in	1.181 in	0.35 lb
80457	T45	0.688 in	0.590 in	1.85 in	1.181 in	0.39 lb
80458	T50	0.688 in	0.590 in	1.85 in	1.181 in	0.45 lb
80459	T55	0.750 in	0.750 in	1.85 in	1.181 in	0.45 lb

3/8" Drive Stubby Universal Tamper Proof Torx[®] Bit Sockets

- For use with tamper proof security fasteners
- Universal joint allows for greater access
- Bits made of S2 steel for strength and durability
- Optimized overall length provides even more access in tight spaces
- Hard stamped size markings
- Bright, full polish chrome finish easily wipes clean and resists corrosion

Cat. No.	Fastener Size	Dim. A: Drive End	Dim. B: Nose
81047	T40	0.740 in	0.740
81048	T45	0.740 in	0.740
81049	T50	0.740 in	0.740
81050	T55	0.740 in	0.740



3/8" DRIVE

0


 \odot

 \odot


RATCHETS DRIVE | SOCKETS TOOLS











FORGE AHEAD