

ASSOCIATED® US MADE PLUG-IN CABLES, BOXES AND ACCESSORIES

FOR TOW & RESCUE PROS

Associated Equipment Booster Cables & Clamps	Competitor Products
OEM Tested and Approved	No OEM Approvals
Targets Professional / Commercial User	Retail is Primary Market
Patented Polarity Indication in Several Models	No Polarity Indication Available
Heavy Duty Bonded "Plastisol" Vinyl Coated Steel Clamps	Retail grade parrot clamps with lower grade wire
100% Copper US made Cable	Imported aluminum or copper mix cable
Cable Jacket Material: 4764 TPE and 6197-78 PVC flexible to -40°F	Light duty jacket – thick jacket/small cable
Grease and chemical resistant clamps / cables	Low grade cable, not rated to survive corrosive environments
Replaceable Copper Jaws	Not Serviceable
Built-in Side Terminal Adapters (PATENTED)	No Side Terminal Adapters Available
Cables Rated in AWG, complies with circular mil standards	Cable Not Rated in AWG
Arc Resistant (fully insulated)	Not Arc Resistant
Strain Relief Guards on most clamps	Not Available



6118-6119

Model 6118

- Heavy-duty 500 Amp fully insulated Clamps with Side Terminal Adapters
- 25' of tangle-free dual-extruded 4 AWG cables
- Made in USA of US and Global Components



6139

Model 6119

- 500 Amp fully insulated Clamps with Side Terminal Adapters
- 30' of tangle-free dual-extruded 4 AWG cables
- Made in USA of US and Global Components



6146

Model 6139

Stainless steel receptacle mounts onto a truck bumper and connects directly to a battery

- Reaches stalled vehicles from front, back or side
- For flush mount version, combine with Model 6125
- Polarized polycarbonate plug won't break in coldest weather
- Patented "Stop/Go safety light"
- Heavy duty stainless steel box
- 25' of tangle-free dual-extruded 4 AWG cables
- Made in USA of US and Global Components

Model 6146

Heavy-Duty Tangle-Free Plug-In Booster Cables

- Extra heavy duty plug-in starting system ideal for volume car starting in extremely cold climates
- 800 Amp solid copper jaw
- For flush mount version, combine with Model 610321
- Polarity Indication
- Heavy duty Stainless Steel Box
- 25' of tangle-free dual-extruded Heavy Duty 1 AWG cables
- Made in USA of US and Global Components



PRODUCT SPECIFICATIONS

KWIKSTART

Model Number	Voltage	Peak AMPS	Cold Cranking AMPS (CCA)	Battery Power	DC Leads	Charger	Limited Warranty	Shipping Dimensions (LxWxH)	Weight (Pounds) Lbs	COO	Page Number
6127	12V	Up to 1100A	Up to 1100A	For Group 24 (Not Included)	8" 4AWG	10A 12V AGM Safe	1 YEAR	16"x17"x30"	48	US	11
6127XL	12V	Up to 1100A	Up to 1100A	For Group 31 (Not Included)	8" 4AWG	10A 12V AGM Safe	1 YEAR	18"x21.5"x30"	54	US	11
6256	12V	1700A	360A	12V/22Ah	32" 4AWG	Auto/500mA	1 YEAR PRORATED	4.25"x18"x11.5"	22	CN	13
6296	12/24V	3400A	720A	12V/44/Ah (2)	66" 2AWG	Auto/1000mA	1 YEAR PRORATED	10"x16.75"x18.25"	44	CN	13
KS400	12V	1700A	360A	12V/22Ah	36" 4AWG	Auto/600mA	1 YEAR PRORATED	17.69"x7.37"x16.75"	25	US9	12
KS401	12V	1700A	360A	12V/22Ah	84" 4AWG	Auto/600mA	1 YEAR PRORATED	17.69"x7.37"x16.75"	26	US9	12
MSK6211	12V	1700A	360A	12V/22Ah	32" 4AWG	Auto/500mA	1 YEAR PRORATED	4.25"x18"x11.5"	25	CN	13

LOAD TESTERS FOR ALL 12V BATTERY TYPES SLA, AGM, EFB, LI-ION

Model Number	Load	Ammeter	Voltmeter	Leads	Clamps	Limited WARRANTY	Shipping Dimensions (LxWxH)	Weight (Pounds) Lbs	COO	Page Number
12-1011	N/A	N/A	6/12V DC DIGITAL	10"	ALLIGATOR	1 YEAR	8.5"x7"x3"	1	CN	22
12-1012	Resistance	N/A	9-15V DC DIGITAL	6"	125A	1 YEAR	9"x11"x3.5"	2	CN	22
12-1015	Resistance	N/A	9-15V DC DIGITAL	6"	125A	1 YEAR	11"x15"x4.25"	3.5	CN	22
12-2415	Resistance	N/A	9-36V DC GRAPHICAL	64"	125A	1 YEAR	18.25"x13.25"x5.5"	7	CN	23
12-2416	N/A	N/A	N/A	N/A	N/A	1 YEAR	4"x3"x7.25"	2	CN	23
6024	125/125A	N/A	0-30V DC ANALOG	2' 14/3	300A	1 YEAR	7"x6"x11"	4	US	24
6026	135A	N/A	0-16V DC ANALOG	2' 14/3	300A	1 YEAR	7"x6"x11"	4	US	25
6028DL	60/125A	N/A	0-16V DC ANALOG	2' 14/2	125A	1 YEAR	7"x6"x11"	4	US	24
6029	125A	N/A	0-16V DC ANALOG	2' 14/2	300A	1 YEAR	7"x6"x11"	4	US	24
6030	125A	N/A	6-19V DIGITAL	2' 14/2	125A	1 YEAR	7"x6"x11"	4	US	25
6030DV	125/125A	N/A	6-30V DIGITAL	2' 14/2	300A	1 YEAR	7"x6"x11"	4	US	25
6031	125A	N/A	0-16V DC ANALOG	2' 14/2	300A	1 YEAR	7"x6"x11"	4	US	25
6033	125A	N/A	7-19V DC ANALOG	2' 14/3	300A	1 YEAR	7"x6"x11"	4	US	24
6034	500A CARBON PILE	4 1/2" 0-500A	0-16V DC ANALOG	2 1/2' 4 AWG	400A	90 DAYS	11"x12.5"x7"	10	CN	26
6036B	1000A CARBON PILE	6" 0-100A	0-16V DC ANALOG	5' 2 AWG	1000A 15 Sec Rating	1 YEAR*	14.75"x15"x15"	32	US	26
6036B-24	1000A CARBON PILE	6" 0-100A	0-32V DC ANALOG	5' 2 AWG	1000A 15 Sec Rating	1 YEAR*	14.75"x15"x15"	32	US	26
6039	600A CARBON PILE	DIGITAL LCD 0-199.99V DC	DIGITAL LCD 0-199.99V D	5.5' 4 AWG	500A	1 YEAR*	16.25"x10.5"x8.6"	17	US	26
6042	500A CARBON PILE	DIGITAL LCD 0-999A	DIGITAL LCD 0-32.0V DC	8' 4 AWG	500A	1 YEAR*	19"x36"x8"	67	US	27
6043	N/A	1A=1mV	N/A	10"	Up to 1000A	90 DAYS	10.5"x4.25"x2"	1	TW	29
6044	500A	DIGITAL 999 A LED	DIGITAL 0-45.0V LED	8' 4 AWG	500A	1 YEAR	24"x14"x14"	23	US	28
6044-C	500A	DIGITAL 999 A LED	DIGITAL 0-45.0V LED	8' 4 AWG	500A	1 YEAR	36"x18"x19"	58	US	28
6044-PC	500A	DIGITAL 999 A LED	DIGITAL 0-45.0V LED	8' 4 AWG	500A	1 YEAR	36"x18"x19"	58	US	28
7136R	1000A CARBON PILE	DIGITAL 0-1999A LED	DIGITAL 0-19.99V LED	5' 2 AWG	1000A 15 Sec Rating	1 YEAR	14.75"x15"x15"	32	US	26

BOOSTER CABLES AND ACCESSORIES

Model Number	Length	Gauge	Circular MIL. Copper	AMP Clamp	Side Terminal Adapters	"Flexi-Spring"	Polarity Indication Safety Lite	SAE Rating	Shipping Dimensions (LxWxH)	Weight (Pounds) Lbs	COO	Page Number
6118	25'	4 AWG	37,044	500A	Yes	N/A	N/A	Heavy-Duty	12"x12"x6"	15	US	30
6119	30'	4 AWG	37,044	500A	Yes	N/A	N/A	Heavy-Duty	12"x12"x6"	17	US	30
6125	5'	4 AWG	37,044	N/A	N/A	N/A	N/A	Heavy-Duty	8.25"x8.25"x4"	3	US	31
6137	5'	4 AWG	37,044	N/A	N/A	N/A	N/A	Heavy-Duty	8.25"x8.25"x4"	4	US	31
6138	25'	4 AWG	37,044	500A	Yes	Yes	Yes	Heavy-Duty	12"x10"x5"	13	US	31
6139	25'	4 AWG	37,044	500A	Yes	Yes	Yes	Heavy-Duty	12"x12"x6"	17	US	30
6141/6141-25	15'/25'	5 AWG	32,900	500A	Yes	Yes	N/A	Aircraft Heavy-Duty	11"x11"x4"	9	US	33
6142	15'	5 AWG	32,900	500A	Yes	Yes	N/A	Aircraft Heavy-Duty	11"x11"x4"	9	US	33
6146	25'	1 AWG	83,600	800A	N/A	Yes	Yes	XX Heavy-Duty	12"x12"x9"	26	US	30
6147	12'	4 AWG	37,044	500A	N/A	Yes	Yes	Heavy-Duty	12"x10"x5"	6	US	31
6148	12'	1 AWG	83,600	800A	N/A	Yes	Yes	Heavy-Duty	12"x12"x9"	6	US	31
6149	5'	1 AWG	83,600	800A	N/A	N/A	N/A	Heavy-Duty	6"x6"x6"	3	US	31
6156	12'	5 AWG	32,900	400A	N/A	No	N/A	Heavy-Duty	11"x11"x4"	7	US	34
6157	12'	5 AWG	32,900	500A	Yes	Yes	N/A	Heavy-Duty	11"x11"x4"	8	US	34
6158	12'	5 AWG	32,900	500A	Yes	Yes	N/A	Heavy-Duty	11"x11"x4"	8	US	34
6159	15'	5 AWG	32,900	500A	Yes	Yes	N/A	Heavy-Duty	11"x11"x5"	9	US	35
6160	20'	4 AWG	37,044	500A	Yes	Yes	N/A	Heavy-Duty	11"x11"x5"	12	US	35
6161	20'	1 AWG	83,600	800A	N/A	Yes	N/A	X-Heavy-Duty	12"x12"x6"	17	US	35
6162	15'	1/0 AWG	100,700	800A	N/A	Yes	N/A	XX Heavy-Duty	10"x12"x5"	16	US	35
6163	25'	1/0 AWG	100,700	800A	N/A	Yes	N/A	XX Heavy-Duty	12"x12"x9"	25	US	35

CLAMPS

Model Number	AMP Clamps	"Flexi-Spring"	SAE Rating	Shipping Dimensions (LxWxH)	Weight (Pounds) Lbs	COO	Page Number
6199	400A	N/A	Heavy-Duty	8.75"x13"x1.5"	1	US	31
6200	ADAPTER	N/A	Heavy-Duty	4"x7"x1"	1	US	31
6202	500A	YES	Heavy-Duty	8.75"x13"x1.5"	2	US	31
6205	800A	YES	Heavy-Duty	8.75"x13"x1.5"	2	US	31
6207	POLARIZED PLUG KIT	N/A	N/A	8.75"x6.5"x1.5"	1	US	31
6208	175A POLY CARB PLUG	N/A	N/A	8.75"x6.5"x1.5"	1	US	31
6216	POLARIZED AN PLUG	N/A - AIRCRAFT	N/A	8.75"x6.5"x1.5"	1	US	33
6217	POWER PLUG	N/A - AIRCRAFT	N/A	8.75"x6.5"x1.5"	9	US	33

ACCESSORIES

Model Number	Description	Shipping Dimensions (LxWxH)	Weight (Pounds) Lbs	COO	Page Number
6038C	Tester Cart for 6039, 6042, 6044, 6036B, 603B-24, 7136R	14.13"x35.13"x5.5"	41	US	29
6075	10 Clamp Set Bus Bar	31"x15"x4.63"	24	US	20
6075CB	10 Clamp Set Circuit Breaker Bus Bar	31"x15"x4.63"	25	US	20
6075S	10 Clamp Set Smart Bus Bar	31"x15"x4.63"	25	US	20
6086	10 Clamp Set Battery Charging Rack	3 Boxes	110	US	21
CC6212	Positive Cable Clamp Covers, Pair	13.25"x9"x7.25"	1	US	14
MS6209	8' Coil Cord OBDII to 12V Power Port Input	13.25"x9"x7.25"	1	CN	14
MS6209-12	12' OBDII to 12V Power Port Input Plus Cable Cover	13.25"x9"x7.25"	1	CN	14
MS6210-12	12' 12V Power Port Input/ Output Plus Cable Cover	13.25"x9"x7.25"	1	CN	14