

# Multi-Function Headlamp

This non-rechargeable Dual-Light™ Multi-function Headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining. Utilizing Bayco's exclusive Dual-Light design, this headlamp combines a tight-beam long-throw spotlight, with a wide-beam close area floodlight. Rated at 180 & 100 lumens respectively, the high and low-brightness spotlight beams on this headlamp are designed for distance illumination. This headlamp also has two wide-beam floodlight settings rated at 140 & 80 lumens. The floodlight spreads out in a wide even pattern of light expressly for the purpose of providing illumination of areas that are close by. Additionally any combination of spotlight & floodlight settings can be selected simultaneously for even greater functionality. The top mounted dual switches provide high/low-brightness spotlight and high/low-brightness floodlight.

**220 Lumens**  
**Dual-Light™**

**180/100 Lumens**  
**Spotlight**

**140/80 Lumens**  
**Floodlight**

Spot High Spot Low Flood High



Flood Low Dual



- Beam distance rated at 158 meters
- Dual brightness spotlight and multiple brightness/color floodlight modes
- Engineered polymer housing
- Powered by 3 AAA batteries (included)



TECHNOLOGY

**NSP 4608B**

# Multi-Function Headlamp



## FEATURES

- 50,000 + hour LED life
- High/low-brightness spotlight – high/low-brightness floodlight – Dual-Light™
- High/low-brightness spotlight
- Focused spotlight beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-Light (spotlight & white floodlight mode at same time) for maximum versatility
- Engineered polymer housing
- Dual switches located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- Waterproof
- Impact & chemical resistant
- Powered by 3 premium AAA alkaline batteries (included)
- Limited Lifetime Warranty

## INCLUDED

- Headlamp
- 3 premium AAA alkaline batteries
- Non-slip elastic head strap



## SPECIFICATIONS

- Lumens: high spotlight-180, low spotlight-100, high floodlight-140, low floodlight-80, dual-light-220
- Run-time: high spotlight-5 hrs, low spotlight-14 hrs, high floodlight-5 hrs, low floodlight-14 hrs, dual-light-4 hrs
- Beam distance: high 158m, low: 115m
- Water rating: IP-X7
- Drop rating: 2 meters
- Width: 2.6in, height: 2.1in, depth: 1.8in, weight: 3.3oz

FL 1 STANDARD	DUAL-LIGHT	HIGH	LOW
	220 LUMENS	180 LUMENS	100 LUMENS
	4h	5h	14h
	158m	158m	115m
	1564cd	1564cd	821cd
	2m		1m



Model	UPC 0 17398
NSP-4608B	80236 9