

STEP DRILLS

- Premium Cobalt M42 for long tool life
- Faster starting with Blair split point
- Angled double flute for faster penetration
- TiN coated for increased tool life & improved hole quality

Part Number	Description	Depth
35400	1/8" to 1/2"	1/8"
35401	3/16" to 1/2"	3/8"
35402	3/16" to 7/8"	1/8"



SPOTWELD DRILL

Remove Spotwelds Fast on All Types of Metals

- Low Speed 800 RPM - Better for UHSS & Boron
- Manual Feed w/ Leverage Handle Increases Cutter Performance (No air power is consumed to advance the cutter, resulting in more torque and faster spotweld removal)
- Adjustable Cutting Depth
- Two 360° Swivel Frame Clamps (Included)
 - 2-5/16" and 5-5/8" depth
- Low Noise
- Built in Comfort Grip
- Includes (1) 8mm Triple-Fluted Solid Carbide Drill Bit
- Additional Sizes of Carbide Spotweld Drills
 - Part No. 11306 (6.5mm)
 - Part No. 11308 (8mm)
 - Part No. 11310 (10mm)
 - Part No. 11312 (12mm)

Specifications

Cutter RPM:	800
Air Pressure:	90 psi
Air Consumption:	4 CFM (113 L/min)
Length:	13-15/16" (346mm)
Height:	9-1/4" (235mm)
Width:	2" (50mm)
Weight:	5.5 lbs (2.5 kg)
Noise Level:	84dB



Part No. 11300

Patented

