

LeakGuard™

A/C SEALER



8oz Cartridge (240 mL)
Services 8 vehicles
Part No. 480308

LeakGuard™ Professional A/C Stop Leak

The ONLY A/C Sealant available that is Certified to meet SAE J2670 Standard!

LeakGuard™ Professional A/C Sealer safely seals leaks in both rubber and metal components. It is compatible with all refrigerants and will not harm recovery machines. Unlike some sealants that react to moisture, LeakGuard™ is an oil based sealant and will not harden, crystallize or clog the A/C system.

- LeakGuard™ is the first and only A/C stop leak that is Certified to meet the SAE J2670 Standard. That is your assurance that LeakGuard™ is safe to use in automotive air conditioning systems and service equipment.
- LeakGuard™ is specifically formulated for slow leaks that can occur over a 6–12 month period.
- It is fully compatible with R-134a and R-12.
- Unlike other sealants that react with moisture, LeakGuard™ is an oil based sealant and will not harden, crystallize or clog the A/C system or service equipment.
- Used as a preventative maintenance, LeakGuard™ will stay in the system as a high quality lubricant until such time that a leak occurs.

FACT: ALL automobile air conditioning systems leak – even brand new vehicles. The State of Minnesota enacted Legislation in January 2009, which requires all manufacturers to post the leakage rate of their vehicles. As vehicles age, the A/C system will begin to leak at various locations. The California Air Resource Board (CARB) estimates that automobile A/C systems leak on average 85 grams (3 ounces) per year. Mobile Air Conditioning Society (MACS) studies have shown that a system that is low in charge (as little as 6 oz.) can increase A/C compressor operating temperature. This results in extra stress on the internal components and compressor clutch assembly that could lead to premature failure and costly repairs.

UV Dye Certified to meet SAE J-2297 Standard and is OEM approved.
For use with UView's Top Selling Spotgun® Injection System.