#### **4334 CUMMINS OIL FILTER PLUG**

Plugs into oil filter preventing oil from spilling when removing oil filter on 2013-2020 Dodge RAM 6.7L Cummins Diesel Heavy-Duty 2500/3500 trucks. Enables Pre-lube of oil filter before installation. U-handle for easy grip. Ridged side for easy removal from oil filter with locking pliers.



#### **DIPSTICK EXTRACTORS**

Removes broken dipsticks without damage. Thread into 5401 adapter to attach to puller for removal

No. Application Ford 4.6L, 5.4L, 5405 6.2L & 6.8L 5407 Dodge 5.7 & 6.1L 5409 GM 4.8L, 5.3L, 5.7L, 6.0L & 6.2L 5401 Puller Adapter Male 3/8" to Female



# 2500 7 PC. 6 PT LUBE

5/8"-18 Thread

#### WRENCH SET

For male hex drain plugs. Offset head w/ anti-slip rubber grip. Chrome vanadium steel.





# 2049 2 PC. SQUARE HEAD DRAIN PLUG SOCKET SET

Services transfer cases, engine oil pans, manual trans & differential drain/fill plugs on Ford, Jeep, Volvo, Peugeot & more.3/8" drive.

No. Size 2036 8mm



# 8762 EURO OIL DRAIN PLUG WRENCH - 14MM X 17MM

Services BMW, Benz (107), Audi & VW, including crankcases & transmissions. Double 14mm male hex & 17mm female hex offset ends. Chrome-moly forged steel. OAL: 9-1/2" (24cm).



services plugs on VW, Audi, Porsche. Chrome-moly forged steel. OAL: 9-1/4" (23cm).



# **1136 JEEP TRANSMISSION DRAIN PLUG SOCKET - 14MM HEX**

Stubby for clearance on 2012+ Jeep Wrangler 6MT. OAL: 30mm





### METRIC HEX DRAIN PLUG SOCKETS

High-torque 2 pc. bit socket design w/ 1/2" drive.

Size 12mm 2052 2054 14mm 2056 17mm 2058 19mm



## **2048 10MM FEMALE SQUARE HEAD SOCKET**

Services male square plugs on BMW, Ford, Toyota, Renault. 3/8" drive.



# 2039 VW/AUDI DRAIN PLUG SOCKET -

### 16MM XZN TAMPERPROOF

12 point, for oil & transmission drain plugs & fasteners on VW, Audi & Porsche. Fits Detroit Diesel flywheel bolts, front crank pulleys & head bolts. 1/2" drive. Compare to Factory Tool: 3357.



## 1320 8 PC. DRAIN PLUG KIT

For removing plastic oil, coolant, and other drain plugs. Won't damage drain plugs. Includes a T-handle with a square drive ball lock and 7 adapters. Packed in blow mold case. Visit ctatools.com for application details.

No.	Application	
1321	GM (#1)	
1322	Ford (#2)	
1323	Ford (#3)	1
1324	Ford/Lincoln (#4)	A
1325	Mercedes (#5)	
1326	Ford/Peugeot/Citroen/ Lincoln/Opel/Toyota (#6)	
1327	BMW (#7)	J
1328	VW, Audi, Porsche (#8)	

#### 1037 VW/AUDI OIL DRAIN PLUG TOOL

Remove plastic oil drain plugs without damage. Widened thumb-grip allows proper torque. Compare to Audi Factory Tool: T10549. Patent No. D804,264.



# 8606 BENZ OIL DRAIN PLUG TOOL

Remove new plastic oil drain plugs without damage. Services 2014-2020 Mercedes Benz C-class, CLS, E-class, GLC & S-class.



#### 8607 GM OIL DRAIN PLUG TOOL

Remove new plastic oil drain plugs without damage. Services GM Acadia, Blazer, CT6, Silverado, Sierra, XT4 & XT5.





## 9250 CADILLAC DRAIN PLUG & OIL **FILTER SOCKET - T45 TORX®**

Low profile for oil filter housings & drain plugs on Cadillac CTS 2003-2004. 3/8" drive w/ 5/8" hex adapter.



# 9573 SUBARU/GM DRAIN PLUG SOCKET - T70 TORX®

5MT 2004+ WRX, 2003+ Legacy, Forester, 2007 STI clutch side trans bolt & brake rotor retaining bolts on 2003+ GM C4500.



# **DIFFERENTIAL PLUG EXTRACTORS**

For removal of female style plugs w/ damaged holes. Fluted design.

No. Applications

5/16" plugs w/ 1/4" square hole 9035 1/2" plugs w/ 3/8" square hole 9037 3/4" plugs w/ 1/2" square hole 9038



#### THREAD RE-CONDITIONING TAPS

ISO type alloy steel tap to clean oil pan & other threads, transfer case & transmission drain plugs. Use w/ CTA #9660 & 9665 Tap Holders.

No.	Size	Application
18111	12mm x 1.25	Infiniti, Lexus, Nissan, Toyota
18112	12mm x 1.75	Ford, GM, GMC, Saturn
18113	1/2" - 20	Dodge, Ford, GM, GMC, Jeep, Mitsubishi
18114	14mm x 1.50	Ford, Honda, Hyundai, Kia, Mazda
18115	12mm x 1.50	BMW, Mercedes Benz
18116	14mm x 1.25	Jeep, Ford Truck
18117	16mm x 1.50	Dodge, Jaguar
18118	18mm x 1.50	Dodge Truck, Toyota, Volvo
18119	22mm x 1.50	Dodge Truck, BMW

# 18200 11 PC. THREAD

## **CLEANING ASSORTMENT**

Includes one each of the following taps: 12mm x 1.25, 12mm x 1.75, 1/2"-20, 14mm x 1.50, 12mm x 1.50, 14mm x 1.25, 16mm x 1.50, 18mm x 1.50, 22mm x 1.50, plus one each #9660 & 9665 tap holders. All packed in plastic tray organizer w/ protective compartments.



# **5070 ADJUSTABLE TAP HOLDER**

Adjustable to fit tap sizes: M6 - M12. Use w/ CTA #18111, 18112, 18113, 18114, 18115 & 18116 & other taps. 3/8" square drive.

