Dynaline Sander

Air-Powered In-Line Finishing Sander



SANDING PADS PAGE 235


ACCESSORIES PAGE 222

BALL-SWIVEL PLUG PAGE 223

> **DYNAJET PAGE 224**

Great on Wood, Composites & Solid Surfaces

- 2,400 strokes per minute at 90 PSIG (6.2 Bar).
- Uses adhesive-backed coated and non-woven nylon sheets and rolls.
- Quality constructed pad is weight-mated to tool for low vibration, smooth operation and superior finishes.
- Comfort platform provides additional hand and wrist support.



In-Line Motion (All models on page)

Sanding Pad can be rotated 360° for adjusting to most efficient

Includes Comfort Platform

position per application.

FOR ABRASIVE SHEETS 2-3/4" x 8" (70 mm x 203 mm) **FOR ABRASIVE ROLLS** 2-3/4" (203 mm) wide SEE PAGES 277, 286



Non-Vacuum

Model 57400

• Includes 2-3/4" wide x 8" long vinyl-face non-vacuum Sanding Pad (57454).



57405 Versatility Kit

Includes 57400 Dynaline; 57852 Sanding Pad (3-2/3" wide x 7" long premium urethane, long nap, Hook-Face pad); plus medium grade (94951) and very fine (94956) abrasive impregnated non-woven nylon sheets.

Model 57407 with Clips

- Includes 2-3/4" wide x 8" long vinyl-face non-vacuum Sanding Pad with clips (57460).
- · Accepts abrasives 2-3/4" wide x 11" long.
- . Up to four abrasive sheets may be attached, ideal for high-production workplaces.



Self-Generated Vacuum

Model 57401

- Includes 2-3/4" wide x 8" long vinyl-face, vacuum sanding pad (57455).
- · Ready for connection to optional portable self-contained dust collection systems.



Central Vacuum

Model 57404

- Includes 2-3/4" wide x 8" long vinyl-face, vacuum sanding pad (57455).
- . Has 1" outside diameter vacuum port for easy central vacuum hose connection.

See page 235 for Dynabrade **Sanding Pads!**



Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57400	.3 (186)	2,400	79 dB(A)	18 (510)	1/4 (6)	1/4" NPT	2.6 (1.2)	7 (178)	3-3/4 (95)
57401	.3 (186)	2,400	79 dB(A)	18 (510)	1/4 (6)	1/4" NPT	2.6 (1.2)	7 (178)	3-3/4 (95)
57404	.3 (186)	2,400	80 dB(A)	18 (510)	1/4 (6)	1/4" NPT	2.6 (1.2)	7 (178)	3-3/4 (95)
57407	.3 (186)	2,400	79 dB(A)	18 (510)	1/4 (6)	1/4" NPT	2.6 (1.2)	7 (178)	3-3/4 (95)

Tune-Up Kit: No. 96107 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)