

# Heavy Duty Pneumatic Tools

## 4-1/2" - 5" Dia. Pistol Grip Disc Sander

### Model 50321 11,000 RPM

- 5/8"-11 male spindle, .7 hp, rear exhaust.
- Includes 50263 Disc Mount Assembly.
- Ideal for use with abrasive impregnated non-woven nylon discs.
- Removable side handle.



Model 50321

## 4" Diameter Pistol Grip Disc Sander

### Model 50324 11,000 RPM

- 3/8"-24 male spindle, .7 hp, rear exhaust.
- Ideally speed-mated to 4" diameter locking-type discs.
- Includes 50192 locking-type pad. Removable side handle.



Model 50324

## 3" Dia. Gearless Cut-Off Wheel Tool

### Model 52420 Front Exhaust

- .5 hp, 20,000 RPM, right angle, safety-lock throttle lever.
- Ideal for cutting metal, fiberglass and plastic.
- 7° lightweight composite offset handle for greater operator comfort and control.



Model 52420

## 7° Offset, 1/4" Collet Die Grinders

- .4 hp, gearless, rear exhaust. Great for left or right hand usage.
- Lightweight, insulated, ergonomic handle.
- Adjustable collar for comfort and control.

### Model 52335 25,000 RPM

### Model 52337 30,000 RPM



Model 52335

## 2" Dia., .4 hp, 7° Offset Disc Sander

### Model 52503 25,000 RPM

- Lightweight, composite, ergonomic handle.
- Includes locking-type pad for 2" diameter locking-type discs.
- Has 1/4"-20 male spindle, rear exhaust.



Model 52503

## .4 hp, 1/4" Chuck Drill

### Model 52836 20,000 RPM

- Air-powered in NEW pistol grip design!
- Powerful high-torque air motor is ideal for countless applications.
- Finger platform on both sides of tool allows increased stability and comfort.
- Ergonomic, compact design for enhanced comfort with textured tactile grip.



Model 52836

Convenient Finger Platform on both sides of tool

Model Number	Motor hp	Motor RPM	Sound Level	Spindle Thread	Air Flow Rate CFM/SCFM	Air Inlet Thread	Hose Size	Air Pressure PSIG	Weight Pound	Length Inch	Height Inch
50321/50324	.7	11,000	79 dB(A)	3/8"-24 male	4/32	1/4" NPT	3/8"	90	2.2	6-5/8	5-5/8
52335	.4	25,000	76 dB(A)	3/8"-24 male	3/18	1/4" NPT	1/4"	90	1.0	6	3-3/4
52337	.4	30,000	79 dB(A)	3/8"-24 male	3/21	1/4" NPT	1/4"	90	1.0	6	3-3/4
52420	.5	20,000	85 dB(A)	3/8"-24 male	4/28	1/4" NPT	3/8"	90	2.2	6	5-1/2
52503	.4	25,000	87 dB(A)	1/4"-20 male	3/20	1/4" NPT	1/4"	90	1.3	9	3-3/4
52836	.4	20,000	78 dB(A)	3/8"-24 male	3/22	1/4" NPT	1/4"	90	1.8	5.9	5