


MATERIAL REMOVAL APPLICATIONS

Dynorbital-Spirit® sanders with a 3/8 inch orbit make quick work of heavy material removal applications. The wide throw sands a greater surface area than general and fine finishing sanders.



3/8" DIA. ORBIT
Aggressive Sanding
 Orange Throttle Lever



NON-VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59100	3 (76)	Vinyl	81 dBA	1.6 (.7)	7 (178)
59005	5 (127)	Vinyl	81 dBA	1.5 (.7)	6.5 (165)
59010	6 (152)	Vinyl	82 dBA	1.6 (.7)	7 (178)
59178	6 (152)	Hook-face	82 dBA	1.6 (.7)	7 (178)

SELF-GENERATED VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59103	3 (76)	Vinyl	84 dBA	1.5 (.7)	8.5 (216)
59008	5 (127)	Vinyl	82 dBA	1.6 (.7)	8.5 (216)
59013	6 (152)	Vinyl	85 dBA	1.7 (.7)	9 (229)

CENTRAL VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59104	3 (76)	Vinyl	79 dBA	1.5 (.7)	7 (178)
59009	5 (127)	Vinyl	83 dBA	1.5 (.7)	7.25 (184)
59014	6 (152)	Vinyl	84 dBA	1.6 (.7)	7.75 (197)
59181	6 (152)	Hook-face	83 dBA	1.6 (.7)	7.75 (197)

Additional Specifications:

Pad Thread 5/16"-24 Male • Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (6 mm)
 Air Flow Rate 14 SCFM (396 L/PM) • Height 3-1/2" (89 mm) • Air Pressure 90 PSIG (6.2 Bar)
 Sound Level is the pressure measurement according to the method outlined in ISO regulation ISO-15744



SPEED

12,000 RPM

POWER

0.3 hp (224 W)



LIFETIME WARRANTY

TECH TIP

For a swirl-free finish, always start the sander on the work surface and stop the sander off the surface.

RELATED PRODUCTS



Sanding Pads
Page 62



Extreme Orange Discs
Page 76



Coupler and Plug Assembly
Page 59



Raptor Vac® Vacuum Systems
Page 50