


GENERAL SANDING

Dynorbital-Spirit® sanders with a 3/16 inch orbit are an excellent choice for general purpose sanding, able to remove material and feather-edge surfaces when combined with a wide range of abrasive grits.



3/16" DIA. ORBIT
General Sanding
Gray Throttle Lever



NON-VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59105	3 (76)	Vinyl	79 dBA	1.4 (.6)	6.5 (165)
59020	5 (127)	Vinyl	80 dBA	1.4 (.6)	6.5 (165)
59025	6 (152)	Vinyl	81 dBA	1.5 (.7)	7 (178)
59179	6 (152)	Hook-face	81 dBA	1.5 (.7)	7 (178)

SELF-GENERATED VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59108	3 (76)	Vinyl	83 dBA	1.4 (.6)	8.5 (216)
59023	5 (127)	Vinyl	82 dBA	1.5 (.7)	8.5 (216)
59028	6 (152)	Vinyl	85 dBA	1.6 (.7)	9 (229)

CENTRAL VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59109	3 (76)	Vinyl	83 dBA	1.4 (.6)	7.25 (184)
59024	5 (127)	Vinyl	81 dBA	1.5 (.6)	7.25 (184)
59029	6 (152)	Vinyl	83 dBA	1.6 (.7)	7.75 (197)
59182	6 (152)	Hook-face	82 dBA	1.6 (.7)	7.75 (197)



SPEED

12,000 RPM

POWER

0.3 hp (224 W)



LIFETIME WARRANTY

Additional Specifications:

Pad Thread 5/16"-24 Male • Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (6 mm)
 Air Flow Rate 14 SCFM (396 L/PM) • Height 3-1/2" (89 mm) • Air Pressure 90 PSIG (6.2 Bar)
 Sound Level is the pressure measurement according to the method outlined in ISO regulation ISO-15744



Faster sanding, finer finishes and lower costs.

Dynabrade Random Orbital Sanding Pads are precision engineered for ULTRA-SMOOTH performance and LONGER LIFE.