


ULTRA-FINE SANDING

Dynorbital-Spirit® sanders with a 3/32 inch orbit are best utilized in fine finishing and surface repair applications. Delicate enough to level clear coats in preparation for buffing and final finishing.



3/32" DIA. ORBIT
Ultra-Fine Sanding
Black Throttle Lever



NON-VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59110	3 (76)	Vinyl	81 dBA	1.3 (.6)	7 (178)
59035	5 (127)	Vinyl	81 dBA	1.4 (.6)	6.5 (165)
59040	6 (152)	Vinyl	82 dBA	1.6 (.7)	7 (178)
59180	6 (152)	Hook-face	80 dBA	1.5 (.7)	7 (178)

SELF-GENERATED VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59113	3 (76)	Vinyl	85 dBA	1.4 (.6)	9 (229)
59038	5 (127)	Vinyl	81 dBA	1.5 (.7)	8.5 (216)
59043	6 (152)	Vinyl	86 dBA	1.5 (.7)	9 (229)

CENTRAL VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59114	3 (76)	Vinyl	84 dBA	1.4 (.6)	7.75 (197)
59039	5 (127)	Vinyl	83 dBA	1.4 (.6)	7.75 (184)
59044	6 (152)	Vinyl	80 dBA	1.5 (.7)	7.75 (197)
59183	6 (152)	Hook-face	81 dBA	1.5 (.7)	7.75 (197)

Additional Specifications:

Pad Thread 5/16"-24 Male • Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (6 mm)
Air Flow Rate 14 SCFM (396 L/PM) • Height 3-1/2" (89 mm) • Air Pressure 90 PSIG (6.2 Bar)
Sound Level is the pressure measurement according to the method outlined in ISO regulation ISO-15744



SPEED

12,000 RPM

POWER

0.3 hp (224 W)



LIFETIME
WARRANTY

RELATED PRODUCTS



Sanding Pads
Page 62



Extreme
Orange Discs
Page 76



Coupler and
Plug Assembly
Page 59



Raptor Vac®
Vacuum
Systems
Page 50