


GEAR-DRIVEN SANDER

Gear-Driven Sanders or "Mudhog" sanders are utilized for quick, aggressive removal and leveling of body filler, glues and coatings. These slow-speed, high-torque sanders have an epicycloidal motion that typically combines with coarse grit abrasives to optimize preparation stages allowing operators to spend less time sanding.

FEATURES

- ▶ Ergonomically designed for low vibration and reduced sound levels
- ▶ Speed control lever is conveniently located for easy thumb adjustment
- ▶ Insulated tool housing reduces cold air transmission to the hand



EPICYCLOIDAL MOTION

For Aggressive Sanding

Model Number	Diameter Inch (mm)	Vacuum Type	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
58442	6 (152)	Non-Vacuum	3/8 (10)	3.6 (1.7)	5.62 (143)	11.5 (293)
58443	6 (152)	Central	3/8 (10)	3.8 (1.7)	5.62 (143)	11.5 (293)
58445	8 (203)	Non-Vacuum	3/8 (10)	3.9 (1.8)	5.56 (142)	12.5 (293)
58446	8 (203)	Central	3/8 (10)	4.3 (2.0)	5.56 (142)	12.5 (319)
900	8 (203)	Non-Vacuum	3/8 (10)	3.6 (1.7)	4.5 (113)	9.37 (238)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG
Maximum Air Flow 23 SCFM / 651 (L/Min)



Model 58442

SPEED
900 RPM

POWER
0.45 hp (336 W)

DIAMETER
6", 8"



Model 58443



LIFETIME WARRANTY



Model 900

SPEED
800 RPM

POWER
0.15 hp (112 W)

DIAMETER
8"



RELATED PRODUCTS



Sanding Pads
Page 62



A/O Film
and Paper
Discs
Page 77



Optional
Vacuum Hose
Assembly
Page 66



M Class
Vacuum
System
Page 53