

# DYNABUG® II SANDER

Compact and lightweight, Dynabug® II Orbital Sanders access tight areas while limiting operator fatigue – especially when sanding on vertical surfaces. Dynabug® II tools are ideal for feathering applications where creating surfaces with excellent mechanical adhesion qualities is critical in preparation for painting and final finish.

## FEATURES

- Designed to be light weight, ergonomic with a comfort platform to provide additional hand and wrist support

### ORBITAL MOTION

For General Sanding



Model Number	Pad Size Inch (mm)	Pad Type	Vacuum Type	Orbit	Sound Level	Weight Pound (kg)	Length Inch (mm)
58500	3 x 4-1/4 (76 x 108)	Hook-face	Non-Vacuum	3/32"	78 dBA	1.7 (.78)	6.8 (171)
58503	3-1/4 x 5 (82 x 127)	Hook-face	Non-Vacuum	3/32"	78 dBA	1.7 (.78)	7.2 (182)
58507	2-2/3 x 6 7/8 (68 x 175)	Vinyl	Non-Vacuum	3/32"	82 dBA	2.2 (.98)	8 (283)
58510	3 x 4 (76 x 102)	Hook-face	Non-Vacuum	3/32"	84 dBA	1.7 (.78)	6.5 (171)
58511	2-2/3 x 6 7/8 (68 x 175)	Vinyl	Non-Vacuum	3/32"	84 dBA	1.8 (.82)	8 (203)
58516	2-2/3 x 7-3/4 (68 x 196)	Hook-face	Non-Vacuum	3/32"	83 dBA	1.8 (.82)	8.5 (215)
58502	3 x 4-1/4 (76 x 108)	Hook-face	Central	3/32"	83 dBA	1.8 (.82)	7 (179)
58505	3-1/4 x 5 (82 x 127)	Hook-face	Central	3/32"	81 dBA	1.8 (.82)	7.5 (190)
58512	2-2/3 x 7-3/4 (68 x 196)	Hook-face	Central	3/32"	84 dBA	1.9 (.86)	8.75 (222)
58513	2-2/3 x 6-7/8 (68 x 175)	Vinyl	Non-Vacuum	3/16"	81 dBA	1.9 (.86)	8.1 (206)
58514	2-2/3 x 7-3/4 (68 x 196)	Hook-face	Non-Vacuum	3/16"	81 dBA	1.9 (.86)	8.6 (218)
58515	2-2/3 x 7-3/4 (68 x 196)	Hook-face	Central	3/16"	80 dBA	2.0 (.91)	8.9 (226)

**Additional Specifications:** Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (6) • Air Pressure 90 PSIG  
Maximum Air Flow 13 SCFM (368 L/Min) • Height 3.7" (94 mm)



Model 58516

### SPEED

3/16" Models 8,000 RPM  
3/32" Models 10,000 RPM

### POWER

0.11 hp (82 W)



Model 58502



**LIFETIME WARRANTY**

## BENEFITS



Dynabug® sanders are an ideal choice for use in feather edging applications. The square pad and delicate orbital motion allow technicians to sand in corners without undercutting. When equipped with a long-nap pad and non-woven nylon abrasives Dynabug® and Dynabug®II sanders are excellent scuffing and blending tools.