

3" DIAMETER BUFFER


Compact and lightweight with a specially engineered ergonomic, co-molded housing that fits naturally in and insulates a technicians hands from cold air transfer.

FEATURES

- ▶ Tool comes mounted with 54021 Adapter (1/4"-20 male thread)
- ▶ Governor-controlled motor maintains speed under load
- ▶ Extended rear exhaust muffler, safety-lock lever, rotary action

INCLUDES

50120 3" diameter Hook-Face Pad
 90027 Terry Cloth Bonnet
 90028 Wool Buffering Bonnet



ROTARY MOTION

For Rotary Buffering



Model 49440

DIAMETER
3" (76 mm)

SPEED
3,200 RPM

POWER
0.4 hp (298 W)

Model Number	Sound Level	Tool Thread	Maximum Air Flow SCFM (L/Min)	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
49440	79 dB(A)	1/4" - 28 Female	26 (736)	1/4 (6)	1.9 (.9)	2.6 (67)	13 (331)

Additional Specifications: Air Inlet Thread 3/8" NPT • Air Pressure 90 PSIG (6.2 Bar)




5" - 8" DIAMETER BUFFER

Dynabrade buffers that utilize planetary gear sets have been specifically designed for demanding, high-torque applications covering large areas like on commercial trucks, busses and delivery vehicles.

FEATURES

- ▶ Planetary gear set is easily lubricated for extended tool life
- ▶ Safety-lock throttle and soft-grip handle both adjust for left or right hand use



ROTARY MOTION

For Rotary Buffering



Model 51392

DIAMETER
6" - 8" (152 mm - 203 mm)

SPEED
2,800 RPM

POWER
1 hp (744 W)

Model Number	Sound Level	Tool Thread	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
51392	78 dB(A)	5/8" - 11 Male	41 (1,167)	3/8 (10)	4.5 (2.1)	3.75 (95)	13.25 (333)

Additional Specifications: Air Inlet Thread 3/8" NPT • Air Pressure 90 PSIG (6.2 Bar)

RELATED PRODUCTS



Dynacut™ Foam Polishing Pads
Page 92



Dynacut™ Wool Polishing Pads
Page 92



Polishing Compounds
Page 92



Mini-Dynorbital® Disc Pads
Page 94