

SANDING PADS

Dynabrade random orbital sanding pads are precision engineered for ultra-smooth performance and longer life. Exclusive single-piece hub design reduces pad vibration and

ensures smooth performance. Premium urethane sanding pads are perfectly weight-mated to Dynabrade tools, and achieve consistent swirl-free finishes. All Dynabrade sanding pads

feature our exclusive single-piece hub design, which reduces pad vibration and ensures smooth performance.



VINYL-FACE




Non-Vacuum

Vacuum

Channel

Ideal for PSA-type disc adhesion. Remove abrasive adhesive paper liner and press abrasive to vinyl-face sanding pad. Available in Non-Vacuum, Vacuum, and Channel Vacuum pads.

HOOK-FACE



Non-Vacuum

Vacuum

Short nap pads for use with reattachable discs. Long nap pads for use with non-woven nylon discs. Available in Non-Vacuum and Vacuum pads.

MULTI-HOLE ABRASIVE



Vacuum

Compatible with many multi-hole disc formats without the need to align vacuum holes. For improved dust-free sanding of body fillers and primer.

GEAR-DRIVEN SANDER PADS

VINYL-FACE

Diameter Inch (mm)	Part Number	Vacuum Type	Max. RPM	Thickness Inches (mm)	Holes	Screws
5 (127)	57761	Non-Vacuum	12,000	3/8 (10)	—	5
6 (152)	57762	Non-Vacuum	12,000	3/8 (10)	—	5
6 (152)	57763	Vacuum	12,000	3/8 (10)	6	5
8 (203)	56234	Non-Vacuum	10,000	1/2 (13)	—	5
8 (203)	56235	Vacuum	10,000	1/2 (13)	8	5

HOOK-FACE

Diameter Inch (mm)	Part Number	Vacuum Type	Max. RPM	Thickness Inches (mm)	Holes	Screws
5 (127)	57760	Non-Vacuum	12,000	3/8 (10)	—	5
6 (152)	57387	Non-Vacuum	10,000	3/8 (10)	—	6
6 (152)	57764	Non-Vacuum	12,000	3/8 (10)	—	5
6 (152)	57765	Vacuum	12,000	3/8 (10)	6	5
8 (203)	56236	Non-Vacuum	10,000	1/2 (13)	—	5
8 (203)	56237	Vacuum	10,000	1/2 (13)	8	5

