



PART NUMBER	COMPUTER NUMBER	DIAMETER	FACING	THREAD SIZE	MAX RPM
60618D	6018	8"	Cloth	5/8 x 11	4,800
60618V	6118	8"	PSA	5/8 x 11	4,800
J60618	6218	8"	Hook	5/8 x 11	4,800

Firm urethane molded sanding pad for medium to heavy stock removal. Thin enough to get into difficult areas. Also available in 5", 6" and 7" diameters.



PART NUMBER	COMPUTER NUMBER	DIAMETER	FACING	THREAD SIZE	MAX RPM
60658D	6058	8"	Cloth	5/8 x 11	4,800
60658V	6158	8"	PSA	5/8 x 11	4,800
J60658	6258	8"	Hook	5/8 x 11	4,800

Medium urethane molded sanding pad that is firm enough for flat surfaces, yet soft enough for curved surfaces. Also available in 5", 6" and 7" diameters.



PART NUMBER	COMPUTER NUMBER	DIAMETER	FACING	THREAD SIZE	MAX RPM
60678D	6078	8"	Cloth	5/8 x 11	3,200
60678V	6178	8"	PSA	5/8 x 11	3,200
J60678	6278	8"	Hook	5/8 x 11	3,200

Soft urethane molded sanding pad that is firm enough for flat surfaces, yet soft enough for curved surfaces.



PART NUMBER	COMPUTER NUMBER	DIAMETER	FACING	THREAD SIZE	MAX RPM
EXP60658D	6088	8"	Cloth	5/8 x 11	4,800
EXP60658V	6188	8"	PSA	5/8 x 11	4,800
JEXP60658	6288	8"	Hook	5/8 x 11	4,800

Medium urethane molded sanding pad with an extremely flexible edge. Designed for feathering and sanding curved surfaces. Also available in 5" and 6" diameters.



PART NUMBER	COMPUTER NUMBER	DIAMETER	FACING	THREAD SIZE	MAX RPM
60658SD	6068	8"	Cloth	5/8 x 11	4,800
60658SV	6168	8"	PSA	5/8 x 11	4,800
J60658S	6268	8"	Hook	5/8 x 11	4,800

Medium urethane molded sanding pad with soft edge for curved surfaces. Also available in 7" diameters.



PART NUMBER	COMPUTER NUMBER	DIAMETER	FACING	THREAD SIZE	MAX RPM
608D	7068	8"	Cloth	5/8 x 11	4,800
608L	7168	8"	PSA	5/8 x 11	4,800
J608	7268	8"	Hook	5/8 x 11	4,800

Firm bonded sanding pad for medium to heavy stock removal. Thin enough to get into difficult areas. Also available in 3", 4", 5", 6" and 7" diameters.



35201 UNION LAKE ROAD - PO BOX 86 - MOUNT CLEMENS - MI - 48046 - USA

800.343.3776 586.792.6001 (phone) 586.792.6006 (fax) ferroind@aol.com

www.FERROIND.com

