

KL-1510

Pair of Jaws, Size 1N

Universal application.

These jaws are designed to be used in conjunction with the spring compressors **KL-0015, KL-0013, KL-0014 and KL-2000.**

Technical Data:

For spring Ø:	80-165mm
Weight (Pair):	1.9kg



KL-1510-SP Pair of jaws size 1N with protective inserts
Like the **KL-1510**, however, supplied with plastic protective inserts.

KL-1520

Pair of Jaws, Size 2N

Universal application.

The jaws are designed to be used in conjunction with the spring compressors **KL-0015, KL-0013, KL-0014 and KL-2000.**

Technical Data:

For spring Ø:	155-195mm
Weight (Pair):	1.9kg



KL-1520-SP Pair of jaws Size 2N with protective inserts
Like the **KL-1520**, however, supplied with plastic protective inserts.

KL-1530

Pair of Jaws, Size 3N

Universal application.

The jaws are designed to be used in conjunction with the spring compressors **KL-0015, KL-0013, KL-0014 and KL-2000.**

Technical Data:

For spring Ø:	180-240mm
Weight (Pair):	3.0kg



KL-1525-SP

Jaw with Protective Insert, Size 2B

Applicable to BMW 3 Series E46, BMW 5 Series E39.

The jaw is designed to be used in conjunction with the spring compressors **KL-0015, KL-0013, KL-0014 and KL-2000.**

Technical Data:

For spring Ø:	155-195mm
Weight (Piece):	0.9kg



KL-1512

Pair of Jaws, Size 1A

Applicable to Audi A4 front axle, Audi A8 rear axle, Porsche, Saab 90/900, Chrysler, Opel/Vauxhall etc.

The jaws are designed to be used in conjunction with the spring compressors **KL-0015, KL-0013, KL-0014 and KL-2000.**

Technical Data:

For spring Ø:	80-150mm
Gewicht (Paar):	1.9kg



KL-1512-SP Pair of jaws Size 1A with protective inserts
Like the **KL-1512**; however, supplied with plastic protective inserts.