

NEW

RAZOR®

Pressure Feed Spray Guns



Premium Performance & Quality

- Superior atomization with automotive and industrial coatings
- For use with light fleet or industrial projects
- Made in the USA and backed by a 3-year warranty

- Air Inlet Size: 1/4 npsm (R 1/4 -19)
- Fluid Inlet: 3/8 npsm (R 3/8-19)
- Max. Fluid Inlet Pressure: 300 psi (2.1 MPa, 21 bar)
- Max. Air Inlet Pressure 100 psi (0.7 MPa, 7 bar)
- Finish: Gray anodized
- Instruction Manual: PN 312412
- Reference p. 40 & 42



HVLP Pressure

Size	Gun PN	Aircap	Nozzle	Needle Assembly	Air Consumption	Applications
1.0 mm	24A525	253824	253792	253769	14.4 CFM at 29 psi (2.0 bar)	Clear and base coats
1.2 mm	24A526	253824	253793	253771	14.4 CFM at 29 psi (2.0 bar)	Clear and base coats
1.4 mm	24A527	253824	253795	253772	14.4 CFM at 29 psi (2.0 bar)	Clear and base coats



Compliant Pressure

Size	Gun PN	Aircap	Nozzle	Needle Assembly	Air Consumption	Applications
1.0 mm	24A528	253825	253816	253769	11.2 cfm at 35 psi (2.4 bar)	Clear, base and primer
1.2 mm	24A529	253825	253817	253771	11.2 cfm at 35 psi (2.4 bar)	Clear, base and primer
1.4 mm	24A530	253825	253819	253771	11.2 cfm at 35 psi (2.4 bar)	Clear, base and primer



Conventional Pressure

Size	Gun PN	Aircap	Nozzle	Needle Assembly	Air Consumption	Applications
1.2 mm	24A531	288451	288295	253772	13.3 cfm at 43 psi (3.0 bar)	Clear and base coats
1.4 mm	24A532	288451	288297	253771	13.3 cfm at 43 psi (3.0 bar)	Clear and base coats
1.8 mm	24A533	288452	288299	253772	13.3 cfm at 43 psi (3.0 bar)	Primer



HVLP Low Pressure

Size	Gun PN	Aircap	Nozzle	Needle Assembly	Air Consumption	Applications
1.2 mm	289233*	253824	253793	288641	14.4 CFM at 29 psi (2.0 bar)	Clear and base coats

*Includes Model 6680 cup assembly and Model 1400 cup pressure regulator