



Gravity Feed Conventional

- Value – Quality guns at affordable prices
- Innovation – A class leader with 29% fewer parts, readily available repair kits, optional 3M™ PPS™ adapters, optional interchangeable cups and lowest trigger pull among guns in its class
- Performance – Unmatched spray pattern size and quality



FX2000

The FX2000 conventional air spray gun delivers an excellent automotive finish when HVLP is not required. This conventional gun has multiple nozzle options and a large spray pattern up to 12 inches. Includes 600 cc aluminum cup, wrench and cleaning brush.

- Air Inlet Size: 1/4 in npsm (R 1/4 - 19)
- Max. Air Inlet Pressure: 29 psi (0.2 MPa, 2.0 bar)
- Pattern Size: 12 in
- Air Consumption: 9.5 CFM at 43 psi (0.3 MPa, 3.0 bar)
- Cup Size: 20 oz (600 cc)
- Weight with cup: 1.1 lb (0.5 kg)
- Finish: Black Nickel
- Instruction Manual: PN 312372
- Reference p. 45



Size	Gun PN	Needle, Nozzle, Aircap Kits	Applications
Conventional FX2000			
1.0 mm	288883	289291	Base and clear coats, light industrial, hobby, spot repair
1.3 mm	288884	289292	Base and clear coats, high solid, single stage
1.4 mm	288885	289293	Base and clear coats, single stage, sealers, low solid clear
1.5 mm	288886	289294	Base and clear coats, sealers, enamels, medium to high viscosity
1.8 mm	288887	289295	Primer, high viscosity

Ultra Mini Aluminum Cup
125 cc



PN 289517 (p. 25)

Mini Aluminum Cup
250 cc




PN 289321 (p. 25)

3M™ PPS™
Adapter



PN 289520 (p. 26)

FX2000, 1.4 needle,
nozzle repair, aircap kit



PN 289293