

Air Control Units

Protection for Air Cylinders & Air Tools



880A Air Control Unit

Highly effective at removing water, oil and contamination to protect air cylinders and air tools. Contains 18C-3R Regulator with a 160 lb inverted gauge and air cock. Regulated outlet and filtered main line outlet included.

PN	Description
6950	Air Control Unit, 75 cfm
U32719	Replacement filter element

- 5 micron filtration
- Air Inlet Size: 1/2 in NPT (f)
- Air Outlet Size: 3/8 in NPT (f) and 1/4 in NPT (f) plugged
- Max. Operating Pressure: 200 psi (13.6 bar)
- Filter Capacity: 75 cfm
- Regulator Capacity: 50 cfm
- Instruction Manual: PN 310603
- Reference p. 58



606A Air Control Unit

Effective at removing water, oil and contamination to protect air cylinders and air tools. Contains 18C-3R Regulator with a 160 lb inverted gauge and air cock. Regulated outlet and filtered main line outlet included.

PN	Description
U06720	Air Control Unit, 120 cfm
19930	Replacement filter element

- 5 micron filtration
- Air Inlet Size: 1/2 in NPT
- Air Outlet Size: 1/4 in NPT
- Max. Operating Pressure: 200 psi (13.6 bar)
- Filter Capacity: 120 cfm
- Regulator Capacity: 50 cfm
- Instruction Manual: PN 310601
- Reference p. 60



606B Air Control Unit

Effective at removing water, oil and contamination to protect air cylinders and air tools. Contains 18C-3R Regulator with a 160 lb inverted gauge and air cock. Regulated outlet and filtered main line outlet with 200 lb gauge included.

PN	Description
6730	Air Control Unit, 120 cfm
19930	Replacement filter element

- 5 micron filtration
- Air Inlet Size: 1/2 in NPT
- Air Outlet Size: 1/4 in NPT
- Max. Operating Pressure: 200 psi (13.6 bar)
- Filter Capacity: 120 cfm
- Regulator Capacity: 50 cfm
- Instruction Manual: PN 310601
- Reference p. 60



606C Air Control Unit

Effective at removing water, oil and contamination to protect air cylinders and air tools. Contains two 18C-3R Regulators with a 160 lb inverted gauge and air cock. Two regulated outlets and a filtered main line outlet with 200 lb gauge included.

PN	Description
6740	Model 606C Air Control Unit
19930	Replacement Filter Element

- 5 micron filtration
- Air Inlet Size: 1/2 in NPT
- Air Outlet Size: 1/4 in NPT
- Max. Operating Pressure: 160 psi (13.6 bar)
- Filter Capacity: 120 cfm
- Regulator Capacity: 50 cfm
- Instruction Manual: PN 310601
- Reference p. 60

REFERENCE

REPLACEMENT PARTS DRAWINGS INDEX

Air Control Units

