

841 Oxygen Sensor Removal & Installation Set

This versatile 11-piece set is used for the for the installation and removal of oxygen sensors on most domestic and import vehicles, and includes the most popular sizes of oxygen sensor sockets.

The Set Includes:

- 1/2" Dr x 29mm x 6pt x 90mm
- 3/8" Dr x 7/8" x 6pt x 90mm
- 1/2" Dr x 27mm x 12pt x 78mm
- 3/8" Dr x 7/8" x 6pt x 80mm
- 3/8" Dr x 1" & 1-1/16" x 74mm
- 1/2" Dr x 7/8" x 50mm
- 3/8" Dr x 7/8" x 50mm
- 1/2" Dr x 1" Hex x 7/8" 6pt
- 1/2" Dr x 22 x 6pt x 88mm
- 3/8" Dr x 22 x 6pt Offset Deep O2
- M18 x 1.5 Spark plug chaser
- Blow Mold Case



842 Seven Piece Oxygen Sensor Socket Set

A comprehensive socket set that enables technicians to easily install or remove oxygen sensors, vacuum switches and oil pressure sending units on a wide variety of domestic vehicles and imports.

This versatile set includes SAE and metric sockets for the most common applications:

- 7/8" - Vacuum Switch Socket
- 7/8" - Oxygen Sensor Socket (Short)
- 7/8" - Oxygen Sensor Socket (Long)
- 1" - Oil Pressure Sending Unit Socket
- 1-1/16" - Oil Pressure Sending Unit Socket
- 27 mm - Oil Pressure Sending Unit Socket
- 29 mm - Vacuum/Pressure Switch Socket



980 Crank Bolt Socket Set

Deep counter-weighted sockets to add more torque to break loose stubborn crank bolts, specifically for Honda and Toyota. The set includes 17mm 19mm 21mm.

- Honda/Acura® models: Accord®, Civic®, Pilot®, CRV®, Odyssey®, CL, TL, Integra®, MDX® vehicles
- Toyota/Lexus® models: Camry®, Corolla®, 4Runner®, Sequoia®, ES300, LS400 vehicles
- Any vehicle with a 17, 19, or 21 mm crank bolt

