

## 25200 Ford Fuel Filter Wrench

- Low profile that allows mechanics to access those tough fuel filters in tight quarters.
- Used for the installation and removal on Ford Power Stroke Diesel and International/Navistar Diesel engines.
- Other wrenches sometimes break off points of the lid due to pressure not being distributed by the wrench, but this tool spreads the force over six points, preventing damage.



## 987 Heavy Duty Three Legged Oil Filter Wrench

- This three leg design is ideal for removing spin-on filters in tight access areas.
- No handle to interfere with removal.
- Long serrated legs driven by a 3/8" extension and ratchet wrap around the filter.
- Fits filters with diameter of 2-1/2" - 4-3/4" (64mm-121mm).



## 988 Three Legged Oil Filter Wrench

- Features gear driven legs to grip and turn the tightest filters.
- Designed for use with 3/8" driver or 3/4" hex wrench.
- Compact design allows for use in tight spaces.
- Removes filters from 2 3/8" - 3 3/4" (60-95 mm).



## 38400 Drain Plug Repair Kit

Kit designed to repair aluminum oil pans with damaged drain plug threads size M12x1.75 commonly found in GM, Ford, and Mazda. The inserts included allow for the original drain plug to be used, instead of aftermarket plug at a different size. Works with drain plugs commonly found in, but not limited to:

GM, Ford and Mazda aluminum Oil Pans.  
 General Motors vehicles  
 1999-2004 CK Engine ASM  
 V8/LR4/4.8V, LM7/5.3T, LQ4/6.0U



- Kit includes: drill bit, counter boring tool, tap, tap guide, insert tool, & 5 inserts.
- Length of inserts included in kit: 9.2mm.
- Effective in repairing stripped drain plugs without leakage.
- Allows user to use original plug instead of a replacement.

