

## 1" Impacttools

| Model                  | Max Torque<br>ft-lb (Nm) | Working Torque<br>Range<br>ft-lb (Nm) | Free Speed<br>rpm        | Weight<br>lb (kg) | Length<br>in (mm) | Average Air<br>Consumption<br>cfm (L/min) | Air<br>Consumption<br>@ Load<br>cfm (L/min) | Sound<br>Pressure /<br>Power<br>dBA | Air Inlet<br>NPTF<br>in | Min Hose<br>Size<br>in (mm) |
|------------------------|--------------------------|---------------------------------------|--------------------------|-------------------|-------------------|---|---|-------------------------------------|-------------------------|-----------------------------|
| <b>1" SQUARE DRIVE</b> |                          |                                       |                          |                   |                   |   |   |                                     |                         |                             |
| 271                    | 1,100 (1491)             | 200 – 900 (272 – 1224)                | 5,500                    | 12.5 (5.67)       | 8.9" (226)        | 9.5 (269)                                 | 39 (1104)                                   | 98.1 / 109.1                        | 3/8"                    | 1/2" (13)                   |
| 285B*                  | 1,475 (2000)             | 100 – 900 (136 – 1220)                | 5,000                    | 24.6 (11.16)      | 13.2" (335)       | 10 (283)                                  | 37 (1048)                                   | 103.4 / 114.4                       | 1/2"                    | 1/2" (13)                   |
| 285B-6                 | 1,475 (2000)             | 100 – 900 (136 – 1220)                | 5,000                    | 27.8 (12.61)      | 20.1" (511)       | 10 (283)                                  | 37 (1048)                                   | 103.4 / 114.4                       | 1/2"                    | 1/2" (13)                   |
| 280*                   |                          | 1,600 (2169)                          | 150 – 1,000 (204 – 1360) | 6,000             |                   | 22 (9.98)                                 | 13" (330)                                   | 10 (283)                            | 55 (1557)               | 109.1 / 122.1               |
| 122.11/2"              | 1/2" (13)                |                                       |                          |                   |                   |   |   |                                     |                         |                             |
| 280-6                  | 1,600 (2169)             | 150 – 1,000 (204 – 1360)              | 6,000                    | 23.8 (10.80)      | 18.5" (470)       | 10 (283)                                  | 55 (1557)                                   | 109.1 / 122.1                       | 1/2"                    | 1/2" (13)                   |
| <b>#5 SPLINE DRIVE</b> |                          |                                       |                          |                   |                   |   |   |                                     |                         |                             |
| 285B-S6*               | 1,475 (2000)             | 100 – 900 (136 – 1220)                | 5,000                    | 27.8 (12.61)      | 20.1" (511)       | 10 (283)                                  | 37 (1048)                                   | 103.4 / 114.4                       | 1/2"                    | 1/2" (13)                   |
| 280-S-6*               | 1,600 (2169)             | 150 – 1,000 (204 – 1360)              | 6,000                    | 23.8 (10.80)      | 18.5" (470)       | 10 (283)                                  | 55 (1557)                                   | 109.1 / 122.1                       | 1/2"                    | 1/2" (13)                   |
| <i>*Not pictured.</i>  |                          |                                       |                          |                   |                   |   |   |                                     |                         |                             |

### 271

#### Air Impactool

The shortest 1" air Impactool is also one of the most powerful. It combines a compact size with high power output, making it ideal for tire changing, spring work, pinion nut removal, tractor pad removal, and shock work.

- Impressive power-to-size ratio
- Up to 1,100 ft-lb of torque
- Pressure-fed lube system for longer service life



### 280-6

#### Air Impactool

High-production truck tire changing requires the brute force only this jumbo hammer impact mechanism delivers. Reach into deep truck wheels easily with this 6" extended anvil wrench, designed for high-production truck tire changing.

- 1,600 ft-lb of maximum torque
- Jumbo power mechanism for power and durability
- In-handle exhaust directs air away from user



### 285B-6

#### Air Impactool

The 285B models combine exceptional power, control and durability. They deliver 1,770 ft-lb of maximum torque @ 120 psi, with 5,250 rpm free speed and a high-efficiency, 6-vane motor. The swept-back 285B handle provides excellent maneuverability.

- Delivers 1,475 ft-lb maximum torque
- Fast-torque™ delivers 1,000 ft-lb in 2 seconds
- Improved feather touch trigger



**Enhanced durability  
for longer life**

