

| Model | Max Torque ft-lb (Nm) | Working Torque Range ft-lb (Nm) | Free Speed rpm | Weight lb (kg) | Length in (mm) | Average Air Consumption cfm (L/min) | Air Consumption @ Load cfm (L/min) | Sound Pressure / Power dBA | Air Inlet NPTF in | Min Hose Size in (mm) |
|----------------------------|--------------------------|---------------------------------------|-------------------|-------------------|-------------------|---|---|-------------------------------------|-------------------------|-----------------------------|
| 1/4" MINI IMPACTOOL | | | | | | | | | | |
| 2101XP | 50 (68) | 25 – 40 (34 – 54) | 11,000 | 1.4 (0.6) | 6.3" (160) | 1.8 (50) | 18.2 (516) | 81.8 / 92.8 | 1/4" | 3/8" (10) |
| 2101XP-QC* | 50 (68) | 25 – 40 (34 – 54) | 11,000 | 1.4 (0.6) | 6.8" (173) | 1.8 (50) | 18.2 (516) | 81.8 / 92.8 | 1/4" | 3/8" (10) |
| 3/8" MINI IMPACTOOL | | | | | | | | | | |
| 2102XP* | 50 (68) | 25 – 40 (34 – 54) | 11,000 | 1.4 (0.6) | 6.3" (160) | 1.8 (50) | 18.2 (516) | 81.8 / 92.8 | 1/4" | 3/8" (10) |
| 3/8" SQUARE DRIVE | | | | | | | | | | |
| 211* | 150 (204) | 20 – 125 (27 – 170) | 10,000 | 2.40 (1.09) | 6.6" (168) | 2.5 (71) | 11 (311) | 104 / 117 | 1/4" | 3/8" (10) |
| 216B | 200 (271) | 15 – 160 (20 – 217) | 8,500 | 2.8 (1.27) | 7.7 (196) | 3 (85) | 19 (538) | 94.8/105.8 | ¼ (6) | 3/8 (10) |
| 212* | 150 (205) | 20 – 125 (27 – 170) | 11,500 | 2.89 (1.31) | 6" (152) | 2.5 (71) | 11 (311) | 97 / 108 | 1/4" | 3/8" (10) |
| 2015MAX | 180 (244) | 45 – 160 (61 – 217) | 9,000 | 3.4 (1.54) | 13.1 (332) | 3.5 (99) | 19 (538) | 96.6/107.6 | 1/4" | 3/8" (10) |
| 2115QTiMAX* | 300 (407) | 25 – 230 (34 – 312) | 15,000 | 2.49 (1.13) | 5.95" (151) | 4 (113) | 17 (481) | 89.7 / 100.7 | 1/4" | 3/8" (10) |
| 2115TiMAX | 300 (407) | 25 – 230 (34 – 312) | 15,000 | 2.48 (1.12) | 5.95" (151) | 4 (113) | 17 (481) | 96.6 / 107.6 | 1/4" | 3/8" (10) |

*Not pictured.

2101XP

1/4" Mini Impactool

Whether you're working in tight spaces or doing finely detailed finish work, our mini tools deliver the power, versatility, and durability you want, in a conveniently smaller size

- Hard-hitting 5-vane motor delivers smooth and robust performance
- Easily accessible forward / reverse switch for one-handed operation



**Fastens conveniently
in hard-to-reach
places**

2101K

1/4" Mini Impactool Kit

- Includes 10-piece 1/4" socket set

2015MAX

Air Impactool

This revolutionary product is unlike any other on the market today. The Hammerhead Low Profile Impactool offers the power and speed of an impact with the reach of a ratchet. The combination of MAX power, MAX control, and MAX access now allows you to use an Ingersoll Rand Impactool for virtually any application. Say goodbye to awkward extensions and swivel sockets, and watch your productivity soar as you conquer tasks in minutes that once took you hours.



MAX Power

With 180 ft-lb max torque and 7,100 rpm, Hammerhead offers more than twice the power of the leading competitor's ratchet.

MAX Control

A feather-touch trigger, two-position forward power regulator, and conveniently located forward/reverse ring provide precise control.

MAX Access

A head height of under 2" and reactionless torque allow you to safely use this powerful tool in tight spaces.

216B

In-line Air Impactool

This durable in-line wrench is handy for the cramped spaces common to small engine repair and other general service work. The butterfly-style throttle valve lets you adjust speed smoothly in either direction in one continuous motion.

- 175 ft-lb max torque
- Contoured composite butterfly throttle for comfort and control
- Recessed regulator dial



2115TiMAX

Air Impactool

The new 2115TiMAX delivers best in class performance for a tool less than six inches long and weighing less than two and a half pounds. The minimal size of this tool will allow greater access to tight spaces, while the minimal weight will reduce operator fatigue all while still delivering MAX performance.



MAX Power

300 ft-lbs max power in reverse – that's best in class power performance

MAX Control

Enhanced power settings, a feather touch trigger and patented push button forward/reverse provide maximum control

MAX Reliability

FREE two-year limited warranty with tool registration

**Best power-to-weight
ratio in its class**