

# Contents

04 |



## Cordless IQ<sup>V</sup>™ Tools and Accessories

Impact Wrenches and Drivers  
Ratchets  
Drills & Screwdrivers  
Other tools  
Batteries and Chargers

14 |



## Air Impact Wrenches

1/4" and 3/8"  
1/2"  
3/4"  
1" (pistol and rear handle)  
Accessories  
Service Kits

34 |



## Air Ratchets

1/2"  
3/8"  
1/4"

38 |



## Air Grinders

Die Grinders  
Wheel Grinders

44 |



## Air Finishing Tools

Air Sanders and Polishers  
Pads, Disks and Bonnets

50 |



## Air Hammers and Accessories

Air Hammer  
Needle Scaler  
Accessoires

54 |



## Air Drills, Screwdrivers and Specialty Tools

Drills  
Screwdrivers  
Specialty Air Tools

62 |



## Accessories

Couplings & Nipples  
Hoses  
Lubricants

## Cordless IQV™ Tools and Accessories | Other tools, Batteries and Chargers

### C1101

Tool only - 20 V



- Cordless Recip Saw
- 3300 spm
- Adjustable guard
- Inline profile for easy access

Available in kits

**C1101EU-K2** Kit  
CCN: 47559320001



12V Recip Saw, Charger, 2 BL1203 (2.0 Ah) Li-Ion Batteries and 6 Blades P4EV-6

### L5110

Tool only - 20 V



- Ultra-bright white LED casts 180 lumens
- Compatible with all IQV20 batteries
- Multi-position head, standing base and hang hook allow for lighting from above or below at any angle
- Run time:  
12.5 hours (BL2012)/  
15 hours (BL2010)/  
22 hours (BL2022)

Also available

### L1110

Tool only - 12 V

### BL1203

12 V - 2.0 Ah Li-Ion



- Performance - Each battery provides 2.0 Ah of 12 V power, intelligently managed by the IQV12 Series system for maximum tool runtime
- Durability - Positive-lock system emits highly audible click when properly secured in tool, helping to eliminate drops and damage
- Ergonomics - Fuel gauge and patent-pending dual side button design for easier battery installation

## Cordless IQV™ Tools and Accessories | Batteries and Chargers

### BL2012

20 V - 2.5 Ah, Li-Ion



- Performance: The BL2012 x2.5 delivers 100% longer run time than its predecessor at the same size and weight.
- Ergonomic: patent-pending dual side button designed for easier battery installation.
- Durability: The intelligent Battery Management System (BMS) allows the battery to communicate with the tool and charger to offer triple battery protection, prevent over loading, over charging and over discharging for longer tool and battery life.

Protection Boot

**BL2005-BOOT**  
CCN: 47510965001

### BL2022

20 V - 5.0 Ah, Li-Ion



- Performance: The BL2022 x5.0 delivers 68% longer run time than its predecessor at the same size and weight.
- Ergonomic: patent-pending dual side button designed for easier battery installation.
- Durability: The intelligent Battery Management System (BMS) allows the battery to communicate with the tool and charger to offer triple battery protection, prevent over loading, over charging and over discharging for longer tool and battery life.

Protection Boot

**BL2010-BOOT**  
CCN: 47510964001

### BC1110-EU

Charger 12 V batteries



- Performance: Brings fully depleted battery to 100% charge in about an hour
- Durability: Engineered composite housing withstands wear, abrasions, drops, and can be securely screw mounted to a wall or toolbox

### BC1121-EU

Charger 12/20 V batteries



- Versatility: One charger for all your Ingersoll Rand batteries, fully compatible with all existing 20 V and 12 V batteries and that can charge USB mobile devices
- Durability: Engineered composite housing withstands wear, abrasions, drops, and can be securely screw mounted to a wall or toolbox

| Ref.  | CCN         | Battery | V  | Strokes per Minute | Strokes Length mm | HH:MM | Lumens | kg   | mm  | dB(A) | m/s <sup>2</sup> /K <sup>(1)</sup> |
|-------|-------------|---------|----|--------------------|-------------------|-------|--------|------|-----|-------|------------------------------------|
| C1101 | 47559324001 | BL1203  | 12 | 3,300              | 14                | -     | -      | 0.97 | 298 | 77.0  | 17.9/7.8                           |
| L5110 | 48489561    | BL2012  | 20 | -                  | -                 | 12:50 | 180    | 0.86 | 236 | -     | -                                  |
| L1110 | 47500109001 | BL1203  | 12 | -                  | -                 | 6:50  | 180    | 0.58 | 217 | -     | -                                  |

<sup>(1)</sup> ISO60745 - 3-axis measurement: vibration level/measurement uncertainty.

Weight to include tool + battery weights

| Ref.      | CCN         | V     | g    |
|-----------|-------------|-------|------|
| BL1203    | 24206179    | 12    | 0.25 |
| BL2012    | 47515903001 | 20    | 0.41 |
| BL2022    | 47515902001 | 20    | 0.72 |
| BC1110-EU | 47499973001 | 12    | -    |
| BC1121-EU | 47507874001 | 12/20 | -    |