

Air Grinders



Air Grinders | Die Grinders

308B
Straight



- 0.25 kW
- 25,000 rpm
- Only 0.46 kg and 172 mm
- Contains: 1/4" and 6 mm collets

302B
Angle



- 0.25 kW
- 20,000 rpm
- Only 0.58 kg and 175 mm
- Contains: 1/4" and 6 mm collets

307B
Straight



- 0.19 kW
- 28,000 rpm
- Only 0.33 kg and 125 mm
- Contains: 1/4" and 6 mm collets

5102MAX
Angle



- 0.30 kW
- 20,000 rpm
- Only 0.64 kg and 178 mm
- Composite housing
- Contains: 1/4" and 6 mm collets

Also available
5108MAX
Straight



- 0.30 kW
- 20,000 rpm
- Only 0.64 kg and 178 mm
- Composite housing
- Contains: 1/4" and 6 mm collets

Ref.	CCN	mm	kWatt	rpm	kg	mm	in	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
308B	48488332	1/4" + 6	0.25	25,000	0.46	172	1/4 NPT	10	3.3	13.20	92.0	3.7/1.2
302B	48488365	1/4" + 6	0.25	20,000	0.58	175	1/4 NPT	10	2.8	10.80	90.0	5.5/1.5
307B	48488316	1/4" + 6	0.19	28,000	0.33	125	1/4 NPT	10	2.8	11.30	83.0	4.5/1.1

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Ref.	CCN	mm	kWatt	rpm	kg	mm	in	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
5102MAX	48488357	1/4" + 6	0.30	20,000	0.64	180	1/4 NPT	10	2.8	11.80	84.1	3.3/1.1
5108MAX	48488340	1/4" + 6	0.30	25,000	0.46	172	1/4 NPT	10	2.8	11.80	83.3	1.8/0.8

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.