

Air Hammers



118MAX

Round shank



- Stroke: 89 mm
- 2,500 blows per minute
- Contains: quick-change retainer

Also available
118MAXH
Hexagonal shank

Available in kits
118MAXK Round shank
CCN: 47125877
118MAXHK Hexagonal shank
CCN: 46816765



Hammer + Quick-Change Retainer and 5 Chisels

Ref.	CCN	bpm	mm	kg	mm	in	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
118MAX	47124490	2,500	89	2.10	314	1/4 NPT	10	1.4	5.50	92.6	4.0/1.4
118MAXH	46816732	2,500	89	2.10	314	1/4 NPT	10	1.4	5.50	92.6	4.0/1.4

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Air Hammers | Round Shank | Needle Scaler | Accessories

122MAX

Round shank



- Stroke: 67 mm
- 3,500 blows per minute
- Contains: quick-change retainer

Also available
122MAXH
Hexagonal shank

Available in kits
122MAXK Round shank
CCN: 47125869
122MAXHK Hexagonal shank
CCN: 46816757



Hammer + Quick-Change Retainer and 5 Chisels

121/Q-EU

Round shank



- Stroke: 58 mm
- 3,000 blows per minute

Also available
121/QH-EU
Hexagonal shank

125-EU

Needle Scaler



- Stroke: 28 mm
- 4,600 blows per minute
- Contains: steel needles

116-EU

Round shank



- Stroke: 67 mm
- 3,500 blows per minute
- Power regulator

Also available
116H-EU
Hexagonal shank

Available in kits
LA426-EU Round shank
CCN: 01328640
LA427-EU Hexagonal shank
CCN: 01328590



Hammer + 6 Chisels

Air Hammers | Accessories

- **115-183** (CCN: 03788510) spring retainer for 116-EU, 116H-EU, LA426-EU and LA427-EU
- **AVC10-183** (CCN: 03010980) spring retainer for 121/Q-EU and 121/QH-EU
- **9512** (CCN: 45563749) quick-change retainer for all models
- **9500** (CCN: 80117427) chisels, round shank (5 pieces)
- **116H-K5** (CCN: 92536093) chisels, hexagonal shank (5 pieces)



115-183



9512



9500

Ref.	CCN	bpm	mm	kg	mm	in	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
122MAX	47124482	3,500	67	1.80	218	1/4 NPT	10	1.4	5.50	94.2	5.5/1.8
122MAXH	46816740	3,500	67	1.80	218	1/4 NPT	10	1.4	5.50	94.2	5.5/1.8
121/Q-EU	01343698	3,000	58	1.59	194	1/4 NPT	10	1.4	7.10	95.3	19.9/4.6
121/QH-EU	01344944	3,000	58	1.59	194	1/4 NPT	10	1.4	7.10	95.3	19.9/4.6
125-EU	01352178	4,600	29	2.83	465	1/4 NPT	8	3.8	7.10	96.6	8.3/1.3
116-EU	01343755	3,500	67	1.54	198	1/4 NPT	10	1.4	7.10	101.4	14.8/2.2
116H-EU	01343904	3,500	67	1.54	198	1/4 NPT	10	1.4	7.10	101.4	14.8/2.2

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.