



A Division of Thiessen Products, Inc.

## INSTRUCTION SHEET FOR TOOL No. 2262

### SPORTSTER & BUELL SPROCKET LOCKER TOOL

For use on all Sportsters 1991- to present (28T & 29T only) For use on all Buell Twins 1994-2002 **NOTE: NOT FOR USE ON XB OR 1125R MODELS**

Use to remove the final drive belt sprockets on Sportsters & Buell's

**CAUTION: NUT IS A LEFT HAND THREAD**

1. Refer to H-D® Service Manual for specifications.
2. Snugly tighten the thumb screw to hold tools position on the sprocket.

**CAUTION: DO NOT ALLOW SCREW TO MAR SPROCKET TEETH.**

3. To remove nut, insert handle of tool on top of the pivot shaft on 1991-2003 XL models. Inboard of the bottom frame tube and attach to sprocket. On 2004 - present models, handle will contact passenger footpeg mount.
4. When tightening nut, the handle of the tool will contact the bottom of the pivot shaft on 1991 - 2003 XL models. On 2004 - present, handle will contact passenger foot peg mount. Tighten to H-D® specifications using JIMS® Socket Nut Tool (No. 5516).



555 DAWSON DRIVE, CAMARILLO, CA 93012 PHONE 805-482-6913 • FAX 805-482-9224  
VISIT US ON THE WEB AT WWW.JIMSUSA.COM



A Division of Thiessen Products, Inc.

## INSTRUCTION SHEET FOR TOOL No. 2262

### SPORTSTER & BUELL SPROCKET LOCKER TOOL

For use on all Sportsters 1991- to present (28T & 29T only) For use on all Buell Twins 1994-2002 **NOTE: NOT FOR USE ON XB OR 1125R MODELS**

Use to remove the final drive belt sprockets on Sportsters & Buell's

**CAUTION: NUT IS A LEFT HAND THREAD**

1. Refer to H-D® Service Manual for specifications.
2. Snugly tighten the thumb screw to hold tools position on the sprocket.

**CAUTION: DO NOT ALLOW SCREW TO MAR SPROCKET TEETH.**

3. To remove nut, insert handle of tool on top of the pivot shaft on 1991-2003 XL models. Inboard of the bottom frame tube and attach to sprocket. On 2004 - present models, handle will contact passenger footpeg mount.
4. When tightening nut, the handle of the tool will contact the bottom of the pivot shaft on 1991 - 2003 XL models. On 2004 - present, handle will contact passenger foot peg mount. Tighten to H-D® specifications using JIMS® Socket Nut Tool (No. 5516).



555 DAWSON DRIVE, CAMARILLO, CA 93012 PHONE 805-482-6913 • FAX 805-482-9224  
VISIT US ON THE WEB AT WWW.JIMSUSA.COM