

CLASSIC 400 SERIES™ COLUMBIAN ECONOMY C-CLAMPS

SAFE AND ECONOMICAL



NOTE:
• COLUMBIAN C-Clamp meets federal spec # GGG-C-406D, Type I, Class A Light Service

FEATURES

DROP FORGED:

- Manufactured for greater strength under regular strength applications

BLACK OXIDE COATING:

- Spindles and pads are treated to resist corrosion

PATENTED DESIGN:

- Frame geometry allows for maximum strength with greater throat depth and lower weight

IDEAL FOR

- Steel Fabrication
- Industrial Maintenance
- Production
- Repair Operations



**DROP FORGED
CONSTRUCTION**



OSCILLATING HEAD



BLACK OXIDE COATING



4400 & 800 SERIES C-CLAMPS

SQUARE THROAT AND STANDARD DEPTH



NOTE:
• 800 Series C-Clamp meets federal spec # GGG-C-406a, Type I, Class A, Grade a, Style 1

FEATURES

SQUARE THROAT DESIGN (4400 SERIES):

- Up to 37% more throat depth than standard deep throat C-Clamps

PERMA-PADS®:

- Exclusive black oxide coated pad swivels and adapts to angular work pieces for tighter holding

REPLACEABLE PARTS:

- Both the spindle and PERMA-PADS® are replaceable and can be individually ordered

DROP FORGED:


- Manufactured for greater strength under regular strength applications

IDEAL FOR

- Steel Fabrication
- Industrial Maintenance
- Production
- Repair Operations



PERMA-PADS®



BLACK OXIDE COATING



**DROP FORGED
CONSTRUCTION**



Stock No.	Model	Nominal Opening Capacity (in.)	Throat Depth (in.)	Clamping Force (lbs.)	Spindle Size (in.)	Net Weight (lbs.)
400 SERIES COLUMBIAN						
20301	H402	0 – 2	2	3,500	1/2	2
20302	H403	0 – 3	2-3/8	3,500	5/8	2
20303	H404	0 – 4	2-3/4	6,200	3/4	3
20304	H406	0 – 6	3-5/8	6,600	3/4	5
20305	H408	0 – 8	4-1/2	6,900	3/4	8
20306	H410	0 – 10	5-3/8	8,000	7/8	12
20307	H412	0 – 12	5-3/4	9,500	7/8	14

Stock No.	Model	Nominal Opening Capacity (in.)	Throat Depth (in.)	Clamping Force (lbs.)	Spindle Size (in.)	Net Weight (lbs.)
4400 SERIES SQUARE THROAT						
14350	4404	0 – 4	4	4,100	3/4	5
14375	4406	0 – 6	5	5,400	3/4	6
14400	4408	2 – 8	6	5,900	3/4	10
800 SERIES STANDARD DEPTH						
14714	802	0-2	1-13/16	2,700	9/16	1
14728	803	0-3	1-15/16	3,000	9/16	2
14742	804	0-4	2-5/16	3,700	5/8	2
14756	806	0-6	2-15/16	4,500	5/8	4
14770	808	0-8	3-7/16	5,200	3/4	7
14784	810	1-1/2-10	3-3/4	6,000	3/4	8
14798	812	1-1/8-12	3-7/8	8,000	3/4	15