

# Service Vehicle

## Standard Features

- Heavy-duty two stage cast iron compressor pump  
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Finned intercooler (two stage only)
- Centrifugal unloader (two stage only)
- Oil sight glass
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Powder coated ASME certified receivers
- Protectively mounted fittings
- Bucket high manual and bottom mounted tank drain
- Large canister intake filter with replaceable filter elements
- High quality special unloading valves to assist in engine starting
- Stainless steel braided discharge hose
- Tank gauge
- Pressure relief safety valve
- Constant run control  
Single stage set 105 – 125 PSI  
Two stage set 145 – 175 PSI
- Pneumatic throttle idle control
- Honda GX Series OHV Engines except for the 18 HP which features the Kohler OVH V-Twin Engine
- Designed, tested and proven to meet the demands of the construction and rental industry



J11HGA-30T

### Single Stage

Model	Pump	HP	Tank Gallon	Drive	CFM @ 125 PSI	CFM @ 150 PSI
K5HGA-30T	K	5.5	30	Recoil Start	8.6	7.9
C6HGA-30T	C	6.5			10.3	9.6
G9HGA-30T	G	9			16.0	14.9
G11HGA-30T		11		18.3	17.3	
J11HGA-30T	J	13		Electric Start	24.0	22.9
J13HGA-30T					28.4	27.1



K5HGA-30T

### Two Stage

Model	Pump	HP	Tank Gallon	Drive	CFM @ 125 PSI	CFM @ 175 PSI
GT9HGB-30T	GT	9	30	Recoil Start	15.7	15.4
GT11HGB-30T		11			16.5	16.3
W11HGB-30T	W	13		Electric Start	19.8	17.6
W13HGB-30T			23.4		20.9	
U18KGB-80T*	U	18	80		39.5	34.7

\*Fuel tank sold separately



GT11HGB-30T

## Options

Air line filter ■ Lubricator ■ Electric start  
Discharge Unloader

Other engine options available upon request  
Other pressures available upon request

UL and CSA are not required for gas engine units.