

Steam Cleaners

Oil Fired Steam Cleaners



- ◆ Heavy Duty Powder Coated Modular Chassis
- ◆ Jenny's Patent Pending Twin Fire Modular Gun Burner
- ◆ Belt Driven Triplex Ceramic Plunger Pump
- ◆ Lighted Panel Mounted Rocker Switches
- ◆ Liquid Tight Junction Box
- ◆ 24 Volt Intrinsically Safe Control Voltage
- ◆ Ground Fault Circuit Interrupter (Single Phase)
- ◆ Nozzle Control
- ◆ High Pressure Relief Valve
- ◆ High Temperature Limit Protection
- ◆ Stainless Steel Cover
- ◆ Stainless Steel Coil Casing Cover
- ◆ Stainless Steel Float Tank
- ◆ High Pressure Adjustable Chemical Injection
- ◆ Round and Flat Steam Nozzles
- ◆ 3/8" Diameter x 50 Foot Quick Coupled Hose

	SJ 70	SJ 100	SJ 120
Pump Output			
Steam Cleaner Pressure (PSI)	100-200	100-200	100-200
Steam Cleaner Volume (GPM)	70 GPH	100 GPH	120 GPH
Steam Cleaner Temperature	325°F	325°F	325°F
Triplex Ceramic Plunger Pump	Standard	Standard	Standard
Belt Drive	Standard	Standard	Standard
Electric Motor			
HorsePower	1	1	1
115 Volt - 1 Phase	Standard	Standard	Standard
230 Volt - 1 Phase	Optional	Optional	Optional
230 Volt - 3 Phase	N/A	Optional	Optional
460 Volt - 3 Phase	N/A	Optional	Optional
575 Volt - 3 Phase	N/A	Optional	Optional
Solution Capacity	Separate Container	Separate Container	Separate Container
Price	Call	Call	Call

These are Real 325°F Steam Cleaners not 250°F Hot Pressure Washers

Steam Cleaners

Gas Fired Steam Cleaners

- ◆ Heavy Duty Powder Coated Modular Chassis
- ◆ Natural Updraft Gas Burner
- ◆ Automatic Electronic Pilot Ignition System
- ◆ Belt Driven Triplex Ceramic Plunger Pump
- ◆ Lighted Panel Mounted Rocker Switches
- ◆ Liquid Tight Junction Box
- ◆ 24 Volt Intrinsically Safe Control Voltage
- ◆ Ground Fault Circuit Interrupter (Single Phase)
- ◆ Nozzle Control
- ◆ High Pressure Relief Valve
- ◆ High Temperature Limit Protection
- ◆ Stainless Steel Cover
- ◆ Stainless Steel Coil Casing Cover
- ◆ Stainless Steel Float Tank
- ◆ Draft Diverter
- ◆ High Pressure Adjustable Chemical Injection
- ◆ Round and Flat Steam Nozzles
- ◆ 3/8" Diameter x 50 Foot Quick Coupled Hose



	SJ 70	SJ 100	SJ 120	SJ 150	SJ 180	SJ 240	SJ 300
Pump Output							
Steam Cleaner Pressure	100-200	100-200	100-200	100-200	100-200	100-200	100-200
Steam Cleaner Volume	70 GPH	100 GPH	120 GPH	150 GPH	180 GPH	240 GPH	300 GPH
Steam Cleaner Temperature	325°F	325°F	325°F	325°F	325°F	325°F	325°F
Triplex Plunger	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Belt Drive Pump	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Electric Motor							
Horsepower	1	1	1	1	1-1/2	1-1/2	1-1/2
115 Volt - 1 Phase	Standard	Standard	Standard	Standard	Standard	Standard	Standard
230 Volt - 1 Phase	Optional	Optional	Optional	Optional	Optional	Optional	Optional
230 Volt - 3 Phase	N/A	Optional	Optional	Optional	Optional	Optional	Optional
460 Volt - 3 Phase	N/A	Optional	Optional	Optional	Optional	Optional	Optional
575 Volt - 3 Phase	N/A	Optional	Optional	Optional	Optional	Optional	Optional
Solution Capacity	Separate Container	Separate Container	Separate Container	Separate Container	Separate Container	Separate Container	Separate Container
Price	Call	Call	Call	Call	Call	Call	Call