

Electric Stationary Compressors

- Auto Start/Stop control with pressure unloader set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Alternator and magnetic starter are standard on all duplex models



U10B-120



GT5B-80V



T25B-240



W5B-80

Two Stage						175 PSI									
Model	Pump	HP	Tank Gallon	Power Supply	Pump RPM	CFM Disp	Del'd Air								
GT2B-60	GT	2	60	115 Volt (through 2 HP) or 230 Volt 1 Phase	450	9.1	7.1								
GT2B-80			80		660	13.4	10.7								
GT3B-60			W		3	60	440	12.2	10.7						
GT3B-80						80	900	18.3	15.2						
W3B-60	GT	5	60		208, 230, 460 or 575 Volt 3 Phase	760	21.1	17.5							
W3B-80			80												
GT5B-60			60												
GT5B-80	W	7-1/2	80			208, 230, 460 or 575 Volt 3 Phase Only	610	38.0	27.2						
GT5B-120			120												
W5B-60			60												
W5B-80	U	10	80				208, 230, 460 or 575 Volt 3 Phase Only	710	43.6	35.2					
W5B-120			120												
U75B-80	T	15	80	208, 230, 460 or 575 Volt 3 Phase Only				520	72.4	56.5					
U75B-120			120												
U10B-80			20								20	120	670	92.6	72.2
U10B-120												120			
T15B-120	25	25	120		208, 230, 460 or 575 Volt 3 Phase Only			780	107.0	83.0					
T15B-240			240												
T20B-120			120												
T20B-240			240												
T25B-120	T	50	120			208, 230, 460 or 575 Volt 3 Phase Only		780	214.0	166.0					
T25B-240			240												

Duplex Single Stage						125 PSI		
Model	Pump	HP	Tank Gallon	Power Supply	Pump RPM	CFM Disp	Del'd Air	
2(K15A)-60	K	3	60	115 Volt (through 2 HP) 230 Volt 1 Phase	870	19.6	12.4	
2(GC5A)-80	GC	10	80		1020	55.6	35.6	

Two Stage						175 PSI		
Model	Pump	HP	Tank Gallon	Power Supply	Pump RPM	CFM Disp	Del'd Air	
2(GT5B)-120	GT	10	120	208, 230, 460 or 575 Volt 3 Phase	900	36.6	30.4	
2(W5B)-120	W				762	42.4	35.0	
2(U10B)-120	U	20	240	208, 230, 460 or 575 Volt 3 Phase Only	710	87.2	70.4	
2(U10B)-240					780	214.0	166.0	