

## Essential Industrial Safety Products



At Justrite, we partner with customers to better understand, anticipate and systematically address the safety challenges you face every day. Our extensive portfolio allows us to think holistically about your organization's vulnerabilities and deliver enterprise-wide compliance.

### Justrite products and expertise help your organization to:

- Reduce fire risks
- Prevent environmental contamination
- Provide emergency relief to injured personnel
- Avoid injuries & accidents
- Avoid fines associated with non-compliance
- Stay in compliance to changing regulations
- Fulfill insurance carrier recommendations
- Improve housekeeping & operational efficiencies

### Approval and Compliance Key

<b>FM</b>	Tested and approved by FM Approvals
<b>UL/ULC</b>	Underwriters Laboratories listed in the U.S. and Canada
<b>ULCLAS</b>	Tested and Approved by UL; Classified to ANSI Z358.1
<b>TÜV</b>	TÜV Technical Inspection Association certified
<b>GS</b>	Geprüfte Sicherheit – safety tested and GS certified by MPA Dresden
<b>CE</b>	Conformité Européenne – European conformity mark that is the manufacturer's declaration that a product meets applicable EC directives
<b>N</b>	Complies with National Fire Protection Association (NFPA) Flammable and Combustible Liquids Code 30
<b>O</b>	Complies with Occupational Safety and Health Administration (OSHA) Regulations
<b>I</b>	Complies with the International Fire Code (IFC)
<b>A</b>	Complies with NFPA 1 Fire Code - 2012 Edition
<b>A9</b>	Complies with NFPA 1 Fire Code - 2009 Edition
<b>H</b>	Complies with NFPA 400 Hazardous Material Code
<b>AN</b>	Meets or exceed American National Standards Institute (ANSI) Z358.1
<b>EN</b>	Complies with European standards EN 14470-1 and EN 14727
<b>ENS</b>	Complies with European standard for showers, EN15154
<b>C</b>	Compressed Gas Association (CGA) P1 Standard for Safe Handling of Compressed Gases in Containers
<b>G</b>	Complies with NFPA 55 Compressed Gases and Cryogenic Fluids Code
<b>U</b>	U.S. Geological Survey High Hazards Zone Requirements
<b>E</b>	Complies with Environmental Protection Agency (EPA) Regulations
<b>S</b>	Supports EPA Spill Prevention, Control and Countermeasures Rule (SPCC)
<b>V</b>	Validated by the EPA Environmental Technology Verification Program





## Type II AccuFlow™ Safety Cans

Go beyond protection and compliance with the added convenience of AccuFlow™ with Safe-Squeeze® trigger for safe and controlled pouring

- Vented design provides smooth, slug-free liquid flow
- Flexible 9-in (229-mm) long metal hose helps control the pour into small openings
- Stainless steel flame arrester prevents flashback ignition
- Two-openings – one for targeted pouring, one with ergonomically designed lift-lever for easy filling
- Sealed lid features automatic positive-pressure relief to protect against explosion
- Large label ID zone provides writing space to identify contents, department location, or individual user name
- Tough powder-coat finish resists chemicals
- Certified by FM Approvals, UL/ULC, and TÜV; meet OSHA and NFPA requirements



Description and Capacity	Hose OD x L	Can OD x H	Approv/Lstg Regulation	Red Can Model
1 gallon (4 L) steel safety can with hose	0.625 x 9 in (16 x 229 mm)	9.5 x 10.5 in (241 x 267 mm)	FM, UL/ULC, TÜV	7210120
2 gallon (7.5 L) steel safety can with hose		9.5 x 13.25 in (241 x 337 mm)		7220120
2.5 gallon (9.5 L) steel safety can with hose		11.75 x 12 in (298 x 305 mm)		7225120
5 gallon (19 L) steel safety can with hose	11.75 x 17.5 in (298 x 445 mm)	7250120		
2.5 gallon (9.5 L) steel safety can with hose	1 x 9 in (25 x 229 mm)	11.75 x 12 in (298 x 305 mm)		7225130
5 gallon (19 L) steel safety can with hose		11.75 x 17.5 in (298 x 445 mm)		7250130