

## Essential Industrial Safety Products



At Justrite, we partner with customers to better understand, anticipate and systematically address the safety challenges you face every day. Our extensive portfolio allows us to think holistically about your organization's vulnerabilities and deliver enterprise-wide compliance.

### Justrite products and expertise help your organization to:

- Reduce fire risks
- Prevent environmental contamination
- Provide emergency relief to injured personnel
- Avoid injuries & accidents
- Avoid fines associated with non-compliance
- Stay in compliance to changing regulations
- Fulfill insurance carrier recommendations
- Improve housekeeping & operational efficiencies

### Approval and Compliance Key

|               |   |
|---------------|---|
| <b>FM</b>     | Tested and approved by FM Approvals   |
| <b>UL/ULC</b> | Underwriters Laboratories listed in the U.S. and Canada   |
| <b>ULCLAS</b> | Tested and Approved by UL; Classified to ANSI Z358.1  |
| <b>TÜV</b>    | TÜV Technical Inspection Association certified  |
| <b>GS</b>     | Geprüfte Sicherheit – safety tested and GS certified by MPA Dresden   |
| <b>CE</b>     | Conformité Européenne – European conformity mark that is the manufacturer's declaration that a product meets applicable EC directives |
| <b>N</b>      | Complies with National Fire Protection Association (NFPA) Flammable and Combustible Liquids Code 30                                   |
| <b>O</b>      | Complies with Occupational Safety and Health Administration (OSHA) Regulations  |
| <b>I</b>      | Complies with the International Fire Code (IFC)   |
| <b>A</b>      | Complies with NFPA 1 Fire Code - 2012 Edition   |
| <b>A9</b>     | Complies with NFPA 1 Fire Code - 2009 Edition   |
| <b>H</b>      | Complies with NFPA 400 Hazardous Material Code  |
| <b>AN</b>     | Meets or exceed American National Standards Institute (ANSI) Z358.1   |
| <b>EN</b>     | Complies with European standards EN 14470-1 and EN 14727  |
| <b>ENS</b>    | Complies with European standard for showers, EN15154  |
| <b>C</b>      | Compressed Gas Association (CGA) P1 Standard for Safe Handling of Compressed Gases in Containers                                      |
| <b>G</b>      | Complies with NFPA 55 Compressed Gases and Cryogenic Fluids Code  |
| <b>U</b>      | U.S. Geological Survey High Hazards Zone Requirements   |
| <b>E</b>      | Complies with Environmental Protection Agency (EPA) Regulations   |
| <b>S</b>      | Supports EPA Spill Prevention, Control and Countermeasures Rule (SPCC)  |
| <b>V</b>      | Validated by the EPA Environmental Technology Verification Program  |





Efficiently wet wipes with a simple pump action.

## Safety Plunger Cans

Moisten cleaning cloths quickly and easily—smart-pump brings more liquid to the top and requires less time between refills

- Dispense flammable liquids and solvents safely, without waste or exposure
- Pump base design leaves less liquid in the bottom before requiring a refill
- Rugged 24-gauge steel cans with powder-coat finish for chemical resistance
- High-density polyethylene container option for greater corrosion resistance
- Approved by FM Approvals and TÜV



Perforated dasher dissipates heat.

| Description and Capacity               | Dasher Assembly | Smart-Pump Assembly | Dasher Dia    | OD x H                          | Approv/Lstg Regulation | Red Model | Yellow Model | CA Prop 65 |
|--|-----------------|---------------------|---------------|---------------------------------|------------------------|-----------|--------------|------------|
| 1 pint (0.5 L) steel plunger can       | steel           | brass & Ryton®      | 5 in (128 mm) | 4.875 x 5.25 in<br>124 x 133 mm | FM, TÜV                | 10008     | 10018        |            |
| 1 quart (1 L) steel plunger can        |                 |                     |               | 7.25 x 5.625 in<br>184 x 143 mm |                        | 10108     | 10118        |            |
| 2 quart (2 L) steel plunger can        |                 |                     |               | 7.25 x 7.875 in<br>184 x 200 mm |                        | 10208     | 10218        |            |
| 1 gallon (4 L) steel plunger can       |                 |                     |               | 7.25 x 10.5 in<br>184 x 267 mm  |                        | 10308     | 10318        |            |
| 1 quart (1 L) polyethylene plunger can | brass           |                     |               | 5.5 x 8.25 in<br>140 x 210 mm   |                        | 14018     | —            | ⚠          |

Ryton® is a registered trademark of Chevron Phillips Chemical Company.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).