


TRUCK AND OFF-ROAD TIRE INFLATION CAGES

*Jaulas para inflado de llantas de camiones y vehículos todo terreno
Cages de gonflage de pneu camion et tout-terrain*



**For reference only. Height A refers to the approximate height to the inside bend of the cage.



4-BAR CAGE 36002
Caja de 4 barras
Cage à 4 barres

5-BAR CAGE 36005
Caja de 5 barras
Cage à 5 barres

3-BAR CAGE 36006
Caja de 3 barras
Cage à 3 barres

7-BAR CAGE 36008
Caja de 7 barras
Cage à 7 barres

Max PSI: 130 Weight: 146 lbs (66.2 kg) Max PSI: 130 Weight: 182 lbs (82.5 kg) Max PSI: 130 Weight: 134 lbs (60.7 kg) Max PSI: 130 Weight: 485 lbs (220 kg)

| Height A** | Width B | Base | Height |
|--------------------|-----------------|-------------------------------|------------------|
| A 43-1/2" (110 cm) | 20-1/2" (52 cm) | 31-1/2" x 26" (80 cm x 66 cm) | 56-1/2" (144 cm) |
| B 43-1/2" (110 cm) | 20-1/2" (52 cm) | 41" x 26" (104 cm x 66 cm) | 56-1/2" (144 cm) |

| Height A** | Width B | Base | Height |
|--------------------|-----------------|----------------------------|------------------|
| D 43-1/2" (110 cm) | 20-1/2" (52 cm) | 26" x 22" (66 cm x 56 cm) | 56-1/2" (144 cm) |
| D 46" (117 cm) | 29" (74 cm) | 34" x 56" (86 cm x 142 cm) | 63" (160 cm) |

EZ TIRE ROTATORS™

*Rotador de neumáticos EZ Tire Rotator™
Rotateur de pneu EZ Tire Rotator™*

Reduces handling, back strain and user fatigue; increases safety. Easily installed or moved to another cage – no fastening required. No assembly required, simply place in the center of the cage. Works as a portable tread inspection and stone removal station outside of cage. Features heavy-duty 2" ball-bearing steel rollers and 1-1/4" thick steel stock for long service. Boxed and UPS shippable. **PATENTED.**



EZ TIRE ROTATOR™ 36014 T114
Rotador de neumáticos EZ Tire Rotator™
Rotateur de pneu EZ Tire Rotator™

Dimensions: 17-1/2" x 25-1/2" (44.5 cm x 64.8 cm) x 2-1/2" (6.6 cm) with ramp Weight: 16 lbs (7.3 kg)

Fits any Ken-Tool® 3-Bar, 4-Bar and 5-Bar Inflation Cage, plus many competitive cages. Quickly rotate assembly inside cage for easy valve access.



EZ TIRE ROTATOR™ WITH RAMP 36018 T118

*Rotador de neumáticos EZ Tire Rotator™ con rampa
Rotateur de pneu EZ Tire Rotator™ avec rampe*

Dimensions: 25" x 25" (64 cm x 64 cm) x 2-5/8" (6.6 cm) with ramp Weight: 21 lbs (9.5 kg)



MAGNUM EZ TIRE ROTATOR™ WITH RAMP 36013 T113

*Rotador de neumáticos Magnum EZ Tire Rotator™ con rampa
Rotateur de pneu Magnum EZ Tire Rotator™ avec rampe*


Dimensions: 25" x 28" (64 cm x 71 cm) x 2-5/8" (6.6 cm) with ramp Weight: 22 lbs (10 kg)

Ramp lifts tire onto rollers with ease. Fits Ken-Tool® Magnum and SuperMagnum Inflation Cages. **PATENTED.**

MAGNUM™ TIRE INFLATION CAGES

*Jaulas para inflado de llantas Magnum™
Cages de gonflage de pneu Magnum™*

Designed to accept the new generation of Super Single and Super Wide-Base truck tires with their higher inflation pressures and air volumes.



**For reference only. Height A refers to the approximate height to the inside bend of the cage.



Magnum™ & SuperMagnum™ Zipper Explosion Tests



MAGNUM™ 5-BAR CAGE 36009 T109

*Caja de 5 barras Magnum
Cage à 5 barres Magnum*

Max PSI: 130 Weight: 211 lbs (96 kg)

| Height A** | Width B | Base | Height |
|------------------|-----------------|----------------------------|--------------|
| 41-1/2" (105 cm) | 24-1/2" (62 cm) | 48" x 30" (122 cm x 76 cm) | 55" (140 cm) |

SUPERMAGNUM™ 5-BAR CAGE 36010 T110

*Caja de 5 barras SuperMagnum
Cage à 5 barres SuperMagnum*

36010 with steel mesh diffuses 93% of blast force from zipper rupture!

Max PSI: 130 Weight: 248 lbs (112.7 kg)

| Height A** | Width B | Base | Height |
|------------------|-----------------|----------------------------|--------------|
| 41-1/2" (105 cm) | 24-1/2" (62 cm) | 48" x 30" (122 cm x 76 cm) | 55" (140 cm) |

PORTABLE MAGNUM™ 2-BAR CAGE 36019 T119

*Caja de 2 barras portátil Magnum
Cage portative à 2 barres Magnum*

Max PSI: 130 Weight: 80 lbs (36.2 kg)

| Height A** | Width B | Base | Height |
|------------------|-----------------|---------------------------------|--------------|
| 49-1/2" (126 cm) | 24-1/2" (62 cm) | 7" x 30" closed (18 cm x 76 cm) | 64" (163 cm) |



C-BEAST BEAD SEATING TOOL 36030

*Outil de portée de talon
Herramienta para calzado de talone*

The Ken-Tool C-Beast lifts the weight of the wheel off the bottom area of the bead of a standing tire/wheel assembly, in order to easily ensure the concentric seating of the bead on a standing Super Single assembly.



Instantly set up and lock on for bead seating.

Instantly release and remove for tire inflation.

Use separately or with any Ken-Tool Inflation Cage.

TIRE INFLATION CAGES:

WARNING: Tire changing can be dangerous, and should be done only by trained personnel using proper tools and equipment as directed by Federal OSHA Standard No. 29 CFR Part 1910.177. Tires may explode during inflation causing injury to operator or bystander. Wear safety goggles. Keep all parts of body outside cage. Use extension hose, clip-on chuck, and remote valve. See supervisor for safety procedures.

WARNING: Do not alter cage in any way. Cage must be freestanding and at least three feet from other objects. Discard cage if bent, cracked, or otherwise damaged. Always wear safety goggles.